

Dampney 105 Thinner SDS Preparation Date (mm/dd/yyyy): 05/2131/2020

Page 1 of 7

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: Dampney Thinner

Product Code(s) : 105

Recommended use of the chemical and restrictions on use

: Paint thinner, solvent

Use pattern: Professional Use Only Recommended restrictions: None Known.

Name, address, and telephone number of the manufacturer:

Dampney Company, Inc.

85 Paris Street

Everett, Massachusetts, U.S.A.

02149

Email: sales@dampney.com

Supplier's Telephone #: (617) 389-2805

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.)

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear liquid. Solvent odor.

Classification:

Flammable Liquid

Specific Target Organ Toxicity (central nervous system)

Category 3

Aspiration toxicant:

Category 1

Label elements

Hazard pictogram(s)







Signal Word

Danger

Hazard statement(s)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed.

H336 May cause drowsiness or dizziness.

Prevention:

P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, lighting, mixing, application equipment.

P242 Use only non-sparking tools.



Dampney 105 Thinner

SDS Preparation Date (mm/dd/yyyy): 05/2131/2020

Page 2 of 7

SAFETY DATA SHEET

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust, fume, gas, mist, vapours, or spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, eye protection, and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER, hospital emergency room or doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER, doctor, or hospital emergency room if you feel unwell.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P370 + P378 In case of fire: Use dry chemical, CO2, water spray (fog) or foam to extinguish.

Storage:

P403 + P233 (S) Store in a cool, well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents and empty container in accordance with local, state and federal regulations. Causes skin irritation

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name		CAS-No	Weight %*	
Dist	illates (Petroleum), Hydrotreated Light	64742-47-8	100	

SECTION 4. FIRST-AID MEASURES

First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.

Eye contact Flush thoroughly with water. If irritation occurs, get medical assistance.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder

contaminated clothing before reuse.

Inhalation Remove from further exposure. For those providing assistance, avoid exposure to

yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-

mouth resuscitation.

Ingestion Seek immediate medical attention. Do not induce vomiting.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Unsuitable Extinguishing Media Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Straight streams of water.

Specific hazards during firefighting Specific extinguishing methods

Do not allow run-off from fire fighting to enter drains or water courses.

Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers,

or drinking water supply. Use a water spray to cool fully closed containers.

Protective Equipment and Precautions for Firefighters

Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.



Dampney 105 Thinner

SDS Preparation Date (mm/dd/yyyy): 05/2131/2020

Page 3 of 7

SAFETY DATA SHEET

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions Eliminate all ignition sources. Maintain adequate ventilation to keep the exposure levels

below the DELS.

Environmental precautions Report spills as required by local and federal regulations. Avoid contaminating ground

and surface water

Methods for Containment Prevent further leakage or spillage if safe to do so. Dike spill area to contain liquid.

Methods for cleaning up Contain liquid and collect with a non-combustible material.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin. Prevent small spills and leakage to avoid slip hazard. Material

can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or ground procedures. However, bonding and grounds may not

eliminate the hazard from static accumulation.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

Keep containers tightly closed in a cool, well-ventilated place.

conditions

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters:

Chemical Name	ACGIH		
Distillates (petroleum) Hydrotreated Light	RCP - TWA: 197 ppm	1200 mg/m³	

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

TWA: Time Weighted Average PEL: Permissible Exposure Limit

Exposure controls

Engineering Measures Ventilation systems. Use adequate ventilation to keep the exposure levels below the

recommended exposure limits.

Individual protection measures, such as personal protective equipment.

General information Eye bath. Safety shower. Washing facilities.

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If engineering controls do not maintain airborne contaminant concentrations at a level

which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory

requirements, if applicable.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear Liquid

Odour : Mild Petroleum Solvent pH : No information available

Melting/Freezing point : Not available Boiling point : 320°F (160°C) Flash point : 109°F (42.77°C)

Evaporation rate (BuAe = 1) : 0.18Lower flammable limit (% by vol.) : 0.7



Dampney Company, Inc. 85 Paris Street Everett, Massachusetts, U.S.A.02149 Email: sales@dampnev.com

Telephone: (617) 389 2805

Dampney 105 Thinner

SDS Preparation Date (mm/dd/yyyy): 05/2131/2020 Page 4 of 7

SAFETY DATA SHEET

Upper flammable limit (% by vol.): 5.6

Vapour pressure : 1.22 mm Hg at 68°F (20°C)

Vapour density (air =1) : 4.9 at 101 kPa

Specific gravity : 0.777 at 60°F (15.6°C)

Weight per gallon : 6.48 lbs Solubility in water : Negligible

Partition coefficient (n-octanol/water)

: Not determined Auto-ignition temperature : 451°F (233°C)

VOC content % : 100

SECTION 10. STABILITY AND REACTIVITY

Reactivity Stable under recommended storage conditions Chemical stability Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid Keep away from heat, sparks, flame and other potential ignition sources.

Incompatible Materials Store away from strong oxidizers.

Hazardous Decomposition Products

Material does not decompose at ambient temperatures.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

None known. Skin contact Eve contact None known.

Inhalation Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

Ingestion Harmful if swallowed.

Component Information

Component information						
	Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation		
	Distillates (Petroleum), Hydrotreated Light	>5000 mg/kg (Rat)	>5000 mg/kg (Rabbit)	>4951 mg/m³ (Rat) 4 h		

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity data: : EL50 - Pseudokirchneriella subcapitata - >1000 mg/l - 72 hours

Persistence and degradability : 80% (28 d, ready biodegradability)

Bio-accumulative potential : No data available. Mobility : No data available.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle in accordance with good industrial hygiene and safety practice.

: Dispose in accordance with all applicable regulations. Methods of Disposal

SECTION 14. TRANSPORTATION INFORMATION

Regulatory	UN Number	UN proper shipping	Transport hazard	Packing Group	Label
Information	OI Number	name	class(es)	Facking Group	Label



Dampney 105 Thinner SDS Preparation Date (mm/dd/yyyy): 05/2131/2020

Page 5 of 7

SAFETY DATA SHEET

49CFR/DOT	UN1263	Paint related material	3	III	FLAMMABLE
49CFR/DOT Additional information	When transported as a limited quantity the maximum net capacity specified in 173.150(b)(2) of the subchapter 49CFR for inner packagings may be increased to 5L (1.3 gallons) 172.102(C)(1)(149) special provision 149.				
TDG	UN1263	Paint related material	3	III	FLAMMABLE
TDG Additional information	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				
IMDG	UN1263	Paint related material	3	III	FLAMMABLE
IMDG Additional information	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				
ICAO/IATA	UN1263	Paint related material	3	Ш	FLAMMABLE
ICAO/IATA Additional information					
	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				
SECTION 15 - REGULATORY INFORMATION					

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). None.

SARA 311/312 Hazard Categories

Immediate Health Hazard Yes
Delayed Health Hazard Yes
Fire Hazard Yes

TSCA (US Toxic Substances Control Act): This product is listed on the TSCA inventory.

Distillates (Petroleum), Hydrotreated Light appears on the following state RTK lists.

Pennsylvania New Jersey

SECTION 16. OTHER INFORMATION

NFPA

Health hazard 1
Flammability 2
Reactivity 0

Legend: ACGIH: American Conference of Governmental Industrial Hygienists

AICS: Australian Inventory of Chemical Substances

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980

CFR: Code of Federal Regulations CSA: Canadian Standards Association DOT: Department of Transportation EC50: Effective Concentration 50%.



Dampney 105 Thinner SDS Preparation Date (mm/dd/yyyy): 05/2131/2020

Page 6 of 7

SAFETY DATA SHEET

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS: Existing and New Chemical Substances

EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System

HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer IECSC: Inventory of Existing Chemical Substances IMDG: International Maritime Dangerous Goods

Inh: Inhalation

KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List

LC: Lethal Concentration

LD: Lethal Dose N/Ap: Not Applicable N/Av: Not Available

NFPA: National Fire Protection Association

NJ: New Jersey

NIOSH: National Institute of Occupational Safety and Health

NOEC: No observable effect concentration

NTP: National Toxicology Program

OECD: Organisation for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PA: Pennsylvania

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

RCRA: Resource Conservation and Recovery Act

RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values
TPQ: Threshold Planning Quantity
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

References

Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2015 (Chempendium, RTECs, HSDB, INCHEM).

OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015

European Chemicals Agency, Classification Legislation, 2015 Material Safety Data Sheet from manufacturer.

Prepared by Dampney Company, Inc.

85 Paris Street Everett, MA 02149

Tel. 617-389-2805 Fax. 617-389-0484 Email mail@dampney.com

Preparation Date (mm/dd/yyyy: 05/21/2020

Other special considerations for handling

: Provide adequate information, instruction and training for operators.



Dampney 105 Thinner SDS Preparation Date (mm/dd/yyyy): 05/2131/2020

Page 7 of 7

SAFETY DATA SHEET

Dampney Company, Inc. 85 Paris Street

Everett MA 02149 U.S.A Telephone: (617) 389-2805



DISCLAIMER

The information and recommendations contained herein are based on data believed to be correct. However, Dampney makes no warranty expressed or implied regarding the accuracy of these data or results to be obtained from the use thereof. Dampney assumes no responsibility for personal injury or property damage caused by use of the material described herein. It is the responsibility of the purchaser or the user to ensure that this material is properly and safely used.

Last Page