



Thurmalox 70C  
SDS Preparation Date (mm/dd/yyyy): 08/07/2018

Page 1 of 11

## SAFETY DATA SHEET

### SECTION 1. IDENTIFICATION

**Product identifier used on the label:** Thurmalox 70C

**Product Code(s)** : 70C

**Recommended use of the chemical and restrictions on use**

: Stainless Steel High Temperature Coating Use pattern: Professional Use Only Recommended restrictions: None  
Known.

**Chemical family** : Mixture. **Name, address, and telephone number of the supplier:**

**Name, address, and telephone number of the manufacturer:**

**Dampney Company, Inc.**

85 Paris Street

Everett, Massachusetts, U.S.A. 02149

Email: sales@dampney.com

Supplier's Telephone #: (617) 389-2805

**24 Hr. Emergency Tel #** : Chemtrec 1-800-424-9300 (Within Continental U.S.)  
Chemtrec 703-527-3887 (Outside U.S.).

### SECTION 2. HAZARDS IDENTIFICATION

**Classification of the chemical**

Black liquid. Solvent odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification:

Flammable Liquids - Category 2

Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory) Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects Specific Target Organ Toxicity, Repeated Exposure - Category 2 (CNS) Skin Irritation - Category 2

Carcinogen - Category 2 Reproductive Toxicity - Category 2

**Label elements**

*Hazard pictogram(s)*



*Signal Word*

**DANGER!**

*Hazard statement(s)*

Highly flammable liquid and vapor. May cause respiratory irritation.

May cause drowsiness and dizziness.

May cause damage to organs through prolonged or repeated exposure. Causes skin irritation.

Suspected of causing cancer.

Suspected of damaging the unborn child.

*Prevention*

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe vapours or spray mist.

Use only outdoors or in a well-ventilated area. Wash thoroughly after handling.

Wear protective gloves/clothing and eye/face protection.

*Response*

If exposed or concerned: Get medical attention/advice.



## SAFETY DATA SHEET

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.  
In case of fire: Use alcohol-resistant foam, carbon dioxide or dry chemical to extinguish.

### Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Other hazards

No OSHA defined hazard classes.

Other hazards which do not result in classification: May be sensitive to static discharge. Burning produces obnoxious and toxic fumes. Direct eye contact may cause slight or mild, transient irritation. Ingestion can cause gastrointestinal irritation, nausea, and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	Common name and synonyms	CAS #	Concentration (% by weight)
tert-Butyl acetate	t-butyl acetate	540-88-5	33.87
p-Chlorobenzotrifluoride	Para-chlorobenzenetrifluoride	98-56-6	24.35
Xylenes	Dimethylbenzene Methyltoluene Xylol	1330-20-7	5.37
Toluene	Methylbenzene Phenylmethane	108-88-3	3.72
n-Butyl alcohol	n-Butanol 1-Hydroxybutane	71-36-3	2.12
Ethylbenzene	Ethylbenzol Phenylethane	100-41-4	1.65
Iron manganese oxide ((Fe,Mn)2O3)	Manganese compounds	75864-23-2	1.14
Acetone	2-Propanone Methyl ketone	67-64-1	1.06

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

## SECTION 4. FIRST-AID MEASURES

### Description of first aid measures

#### Ingestion

: IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. Material is an aspiration hazard. Guard against aspiration into lungs by having the individual turn on their left side. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

#### Inhalation

: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

#### Skin contact

: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

#### Eye contact

: In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.

### Most important symptoms and effects, both acute and delayed

: May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. May cause drowsiness and dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Causes skin irritation. Symptoms may include redness, itching and swelling. Direct eye contact may cause slight or mild, transient irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Suspected of causing cancer.

### Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. This product is a CNS depressant.



## SAFETY DATA SHEET

### SECTION 5. FIRE-FIGHTING MEASURES

#### Extinguishing media

*Suitable extinguishing media:* Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

*Unsuitable extinguishing media:* Do not use water jet, as this may spread burning material.

#### Special hazards arising from the substance or mixture / Conditions of flammability

: Highly flammable liquid and vapor. Keep away from heat and flame. This product will accumulate static charge by flow, splashing or agitation. Vapors may travel considerable distance to a source of ignition and flash back. Vapours are heavier than air and collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

#### Flammability classification (OSHA 29 CFR 1910.106)

: Flammable Liquids - Category 2

#### Hazardous combustion products

: Carbon oxides ; Other unidentified organic compounds.

#### Special protective equipment and precautions for firefighters

*Protective equipment for fire-fighters*

: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

#### Special fire-fighting procedures:

Move containers from fire area if safe to do so. Use water spray to cool unopened containers. Avoid spreading burning liquid with water spray used for cooling purposes. Do not allow run-off from fire fighting to enter drains or water courses. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Dike for water control.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures:

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapour or mist. Restrict access to area until completion of clean-up. Remove all sources of ignition. All persons dealing with the clean-up should wear the appropriate personal protective equipment. For personal protection see section 8.

#### Environmental precautions:

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. For large spills, dike the area to prevent spreading.

#### Methods and material for containment and cleaning up

: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Contaminated absorbent material may pose the same hazards as the spilled product. Pick up and transfer to properly labeled containers. Contact the proper local authorities.

#### Special spill response procedures

: In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887.

EPA/CERCLA Reportable quantity (RQ): Xylene (100 lbs / 45.4 kg)

Ethylbenzene (1000 lbs / 454 kg)

Toluene (1000 lbs / 454 kg)

Acetone and tert-butyl acetate (5000 lbs / 2270 kg)

### SECTION 7. HANDLING AND STORAGE

#### Precautions for safe handling:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat and flame. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Bond and ground transfer containers and equipment. Use explosion-proof electrical and ventilating equipment. Use non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection. Avoid breathing vapour or mist. Do not ingest. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials. Encourage good housekeeping and personal hygiene.

#### Conditions for safe storage :

Store in well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Store away from incompatibles and out of direct sunlight. Take measures to prevent the build up of electrostatic charge. Storage area should be clearly identified, clear of obstruction and



## SAFETY DATA SHEET

accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

**Incompatible materials** :  
Strong oxidizers, acids and bases.

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Exposure Limits:

Chemical Name	ACGIH TLV		OSHA PEL	PEL STEL
	TWA	STEL		
tert-Butyl acetate	200 ppm	N/Av	200 ppm (950 mg/m <sup>3</sup> )	N/Av
p-Chlorobenzotrifluoride	N/Av	N/Av	N/Av	N/Av
Xylenes	100 ppm	150 ppm	100 ppm (435 mg/m <sup>3</sup> )	N/Av
Toluene	20 ppm	N/Av	200 ppm	300 ppm (Ceiling)
n-Butyl alcohol	20 ppm	N/Av	100 ppm (300 mg/m <sup>3</sup> )	N/Av
Ethylbenzene	20 ppm	N/Av	100 ppm (435 mg/m <sup>3</sup> )	N/Av
Iron manganese oxide ((Fe,Mn)2O3)	N/Av	N/Av	N/Av	N/Av
Acetone	250 ppm	500 ppm	1000 ppm (2400 mg/m <sup>3</sup> )	N/Av

#### Exposure controls

##### Ventilation and engineering measures

: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

**Respiratory protection:** If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

##### Skin protection

: Wear protective gloves. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

##### Eye / face protection

: Chemical splash goggles are recommended.

**Other protective equipment** : Ensure that eyewash stations and safety showers are close to the workstation location.

Other equipment may be required depending on workplace standards.

##### General hygiene considerations

: Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Black liquid
Odour	: Solvent odor.
Odour threshold	: N/Av
pH	: N/Av
Melting/Freezing point	: N/Av
Initial boiling point and boiling range	: 55-155°C (131-145°F)
Flash point	: -20 - 42.77°C (-4 - 109°F)
Flashpoint (Method)	: Closed cup
Evaporation rate (BuAe = 1)	: 0.887 times slower than n-Butyl acetate
Flammability (solid, gas)	: N/Av
Lower flammable limit (% by vol.)	: N/Av
Upper flammable limit (% by vol.)	: N/Av
Oxidizing properties	: None known.
Explosive properties	: Not explosive
Vapour pressure Vapour density	: >1



Thurmalox 70C  
SDS Preparation Date (mm/dd/yyyy): 08/07/2018

Page 5 of 11

## SAFETY DATA SHEET

Relative density / Specific gravity : 1.12832  
Solubility in water : N/Av  
Other solubility(ies) : N/Av  
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution : N/Av  
Auto-ignition temperature : N/Av  
Decomposition temperature : N/Av  
Viscosity : 300 cSt at 40°C  
Volatiles (% by weight) : 71.8%  
Volatile organic Compounds (VOC's) : 3.46lbs/gal

Other physical/chemical comments :None reported by the manufacturer.

### SECTION 10. STABILITY AND REACTIVITY

#### Reactivity

: Not normally reactive.

#### Chemical stability

: Stable under normal conditions.

#### Possibility of hazardous reactions

: Hazardous polymerization does not occur. May be sensitive to static discharge.

#### Conditions to avoid

: Keep away from heat, sparks and flame. Take precautionary measures against static discharge. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials.

**Incompatible materials** : Strong oxidizers, acids and bases.

#### Hazardous decomposition products

: See Section 5 (Fire Fighting Measures).

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure:

Routes of entry inhalation : YES  
Routes of entry skin & eye : YES  
Routes of entry Ingestion : YES  
Routes of exposure skin absorption : NO

#### Potential Health Effects:

#### Signs and symptoms of short-term (acute) exposure

##### Sign and symptoms Inhalation:

May cause respiratory irritation. Symptoms may include sore throat, running nose and shortness of breath. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness.

##### Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Causes symptoms similar to those listed for inhalation.

##### Sign and symptoms skin

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Skin Irritation - Category 2  
Causes skin irritation. Symptoms may include mild redness and swelling.

##### Sign and symptoms eyes

: Direct eye contact may cause slight or mild, transient irritation.

#### Potential Chronic Health Effects:

Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

**Mutagenicity:** Not expected to be mutagenic in humans.

**Carcinogenicity:** This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Carcinogenicity - Category 2 Suspected of causing cancer. Contains Ethylbenzene. Ethylbenzene is classified as carcinogenic by IARC (Group 2B) and ACGIH (Category A3).

#### Reproductive effects & Teratogenicity



Thurmalox 70C  
SDS Preparation Date (mm/dd/yyyy): 08/07/2018

Page 6 of 11

### SAFETY DATA SHEET

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:  
Reproductive Toxicity - Category 2 Suspected of damaging the unborn child.  
**Sensitization to material:** Not expected to be a skin or respiratory sensitizer.  
**Specific target organ effects:** Eyes, skin, respiratory system, digestive system, central nervous system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification:

Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory) May cause respiratory irritation.

Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects May cause drowsiness and dizziness.

Specific Target Organ Toxicity, Repeated Exposure - Category 2 May cause damage to organs through prolonged or repeated exposure.

Contains Toluene.

Toluene may cause damage to the brain and nervous system through prolonged or repeated exposure, if inhaled.

**Medical conditions aggravated by overexposure**

: Pre-existing skin, eye, respiratory and central nervous system disorders.

**Synergistic materials:** None reported by the manufacturer.

**Toxicological data :**

There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data. See below for individual ingredient acute toxicity data.

Chemical name	LC50(4hr) inh, rat	LD50	
		(Oral, rat)	(Rabbit, dermal)
tert-Butyl acetate	>2230 mg/m <sup>3</sup>	4100 mg/kg	>2000 mg/kg
p-Chlorobenzotrifluoride	33 mg/L 4 h	13 g/kg	>2000 mg/kg
Xylenes	6,350 ppm (27.6 mg/L) (vapours)	3253 mg/kg	12 180 mg/kg
Toluene	7,585 ppm (28.1 mg/L) (vapour)	5580 mg/kg	12 125 mg/kg
n-Butyl alcohol	8,000 ppm (24.3 mg/L) (vapour)	790 - 4360 mg/kg	3402 mg/kg
Ethylbenzene	4,000 ppm (17.4 mg/L) (vapour)	3500 mg/kg	15 380 mg/kg
Iron manganese oxide ((Fe,Mn)2O3)	N/Av	N/Av	N/Av
Acetone	30,000 ppm (71 mg/L) (vapour)	5800 mg/kg	> 15 800 mg/kg

**Other important toxicological hazards**

: None known or reported by the manufacturer.

### SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

: Contains material that may be harmful in the environment. Should not be released into the environment. See the following tables for the substance's ecotoxicity data.

**Ecotoxicity data:**

Ingredients	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
tert-Butyl acetate	540-88-5	240 mg/L (Rainbow trout)	N/Av	N/Av
p-Chlorobenzotrifluoride	98-56-6	3 mg/L (Danio rerio)	N/Av	None.
Xylenes	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.
Toluene	108-88-3	5.4 mg/L (pink salmon)	1.4 - 4.0 mg/L	None.
n-Butyl alcohol	71-36-3	1376 mg/L (Fathead minnow)	N/Av	None.
Ethylbenzene	100-41-4	4.2 mg/L (Rainbow trout)	1.13 mg/L/30 days	None.
Iron manganese oxide ((Fe,Mn)2O3)	75864-23-2	N/Av	N/Av	None.
Acetone	67-64-1	6210 mg/L (Fathead minnow)	N/Av	None.



**SAFETY DATA SHEET**

Ingredients	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
tert-Butyl acetate	540-88-5	340 mg/L (Daphnia magna)	N/Av	None.
p-Chlorobenzotrifluoride	98-56-6	2mg/L (Daphnia magna)	N/Av	None.
Xylenes	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.
Toluene	108-88-3	3.78 mg/L Ceriodaphnia (water flea)	0.53 - 1 mg/L	None.
n-Butyl alcohol	71-36-3	1328 mg/L (Daphnia magna)	4.1 mg/L	None.
Ethylbenzene	100-41-4	1.81 mg/L (Daphnia magna)	N/Av	None.
Iron manganese oxide ((Fe,Mn)2O3)	75864-23-2	N/Av	N/Av	None.
Acetone	67-64-1	15 800 mg/L (Daphnia magna)	1660 mg/L	None.

Ingredients	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
tert-Butyl acetate	540-88-5	16 mg/L (Green algae)	2.3 mg/L (Green algae)	None.
p-Chlorobenzotrifluoride	98-56-6	>0.41mg/L (Green algae)	0.41 mg/L (Green algae)	None.
Xylenes	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.
Toluene	108-88-3	N/Av	10 mg/L/72hr (Green algae)	None.
n-Butyl alcohol	71-36-3	225 mg/L/96hr (Green algae)	129 mg/L/96hr	None.
Ethylbenzene	100-41-4	3.6 mg/L/96hr (Green algae)	3.4 mg/L/96hr	None.
Iron manganese oxide ((Fe,Mn)2O3)	75864-23-2	N/Av	N/Av	None.
Acetone	67-64-1	7000 mg/L/96hr (Green algae)	N/Av	None.

**Persistence and degradability**

No data is available on the product itself.

**Bioaccumulation potential** : No data is available on the product itself.

Components	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
tert-Butyl acetate (CAS 540-88-5)	1.38	7
p-Chlorobenzotrifluoride (CAS 98-56-6)	3.7 at 25 °C	121-202
Xylenes (CAS 1330-20-7)	3.12 - 3.2	0.6 - 15
Toluene (CAS 108-88-3)	2.65	90
n-Butyl alcohol (CAS 71-36-3)	0.88	0.64 species: freshwater fish





Thurmalox 70C  
 SDS Preparation Date (mm/dd/yyyy): 08/07/2018

**SAFETY DATA SHEET**

Ethylbenzene (CAS 100-41-4)	3.15	15 species: fish
Iron manganese oxide((Fe,Mn)2O3) CAS 75864-23-2)	N/Ap	N/Ap
Acetone (CAS 67-64-1)	0.24	0.69 species: fish

**Mobility in soil**

: No data is available on the product itself.

**Other Adverse Environmental effects**

: None known or reported by the manufacturer.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Handling for Disposal** : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

**Methods of Disposal RCRA**

: Dispose in accordance with all applicable regulations.

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

**SECTION 14. TRANSPORTATION INFORMATION**

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1263	Paint	3	II	
<b>Additional information</b>	When transported as a limited quantity the maximum net capacity specified in 173.150(b)(2) of the subchapter 49CFR for inner packagings may be increased to 5L (1.3 gallons) 172.102(C)(1)(149) special provision 149.				
TDG	UN1263	Paint	3	II	
<b>Additional information</b>	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				
IMDG	UN1263	Paint	3	II	
<b>Additional information</b>	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				
ICAO/IATA	UN1263	Paint	3	II	
<b>Additional information</b>	Refer to ICAO/IATA Packing Instruction.				

**Special precautions for user**

: Keep away from heat, sparks and open flame. - No smoking.

**Environmental hazards:** See ECOLOGICAL INFORMATION, Section 12.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not available.

**SECTION 15 - REGULATORY INFORMATION**

**US Federal Information:**

Components listed below are present on the following U.S. Federal chemical lists:





**SAFETY DATA SHEET**

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
tert-Butyl acetate	540-88-5	Yes	5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate)	N/Av	No	N/Ap
p-Chlorobenzotrifluoride	98-56-6	Yes	N/Av	N/Av	No	N/Av
Xylenes	1330-20-7	Yes	100 lb/ 45.4 kg	None.	Yes	1%
Toluene	108-88-3	Yes	1000 lb/ 454 kg	None.	Yes	1%
n-Butyl alcohol	71-36-3	Yes	5000 lb/ 2270 kg	None.	Yes	1%
Ethylbenzene	100-41-4	Yes	1000 lb/ 454 kg	None.	Yes	0.1%
Iron manganese oxide ((Fe,Mn)2O3)	75864-23-2	Yes	N/Av	N/Av	No	N/Av
Acetone	67-64-1	Yes	5000 lb/ 2270 kg	None.	No	N/Av

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

**US State Right to Know Laws:**

The following chemicals are specifically listed by individual States:

Ingredients	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
tert-Butyl acetate	540-88-5	No	N/Av	Yes	Yes	Yes	Yes	Yes	Yes
p-Chlorobenzotrifluoride	98-56-6	No	N/Av	No	No	No	No	No	No
Xylenes	1330-20-7	No	N/Av	Yes	Yes	Yes	Yes	Yes	Yes
Toluene	108-88-3	No	Developmental	Yes	Yes	Yes	Yes	Yes	Yes
n-Butyl alcohol	71-36-3	No	N/Av	Yes	Yes	Yes	Yes	Yes	Yes
Ethylbenzene	100-41-4	Yes	Cancer	Yes	Yes	Yes	Yes	Yes	Yes
Iron manganese oxide ((Fe,Mn)2O3)	75864-23-2	No	N/Av	No	No	No	No	No	No
Acetone	67-64-1	No	N/Av	Yes	Yes	Yes	Yes	Yes	Yes

**Canadian Information:**

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL). WHMIS Classification: See Section 2.

**International Information:**

Components listed below are present on the following International Inventory list:

Ingredients	CAS #	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
tert-Butyl acetate	540-88-5	208-760-7	Present	Present	(2)-735; (2)-731	KE-04180	Present	HSR001094
p-Chlorobenzotrifluoride	98-56-6	202-681-1	Present	Present	(3)-53	KE-05928	Present	HSR005269 (dilution)
Xylenes	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983



Thurmalox 70C  
SDS Preparation Date (mm/dd/yyyy): 08/07/2018

Page 10 of 11

### SAFETY DATA SHEET

Toluene	108-88-3	203-625-9	Present	Present	(3)-2	KE-33936	Present	HSR001227
n-Butyl alcohol	71-36-3	200-751-6	Present	Present	(2)-3049	KE-03867	Present	HSR001096
Ethylbenzene	100-41-4	202-849-4	Present	Present	(3)-60; (3)-28	KE-13532	Present	HSR001151
Iron manganese oxide((Fe,Mn)2O3)	75864-23-2	No data available.	No data available.	No data available.	No data available.	No data available.	No data available.	No data available.
Acetone	67-64-1	200-662-2	Present	Present	(2)-542	KE-29367	Present	HSR001070

### SECTION 16. OTHER INFORMATION

**Legend:**

ACGIH: American Conference of Governmental Industrial Hygienists  
AICS: Australian Inventory of Chemical Substances  
CA: California  
CAS: Chemical Abstract Services  
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980  
CFR: Code of Federal Regulations  
CSA: Canadian Standards Association  
DOT: Department of Transportation  
EC50: Effective Concentration 50%.  
EINECS: European Inventory of Existing Commercial chemical Substances  
ENCS: Existing and New Chemical Substances  
EPA: Environmental Protection Agency  
HMIS: Hazardous Materials Identification System  
HSDB: Hazardous Substances Data Bank  
IARC: International Agency for Research on Cancer  
IECSC: Inventory of Existing Chemical Substances  
IMDG: International Maritime Dangerous Goods Inh: Inhalation  
KECI: Korean Existing Chemicals Inventory  
KECL: Korean Existing Chemicals List  
LC: Lethal Concentration  
LD: Lethal Dose  
N/Ap: Not Applicable  
N/Av: Not Available  
NFPA: National Fire Protection Association  
NJ: New Jersey  
NIOSH: National Institute of Occupational Safety and Health  
NOEC: No observable effect concentration  
NTP: National Toxicology Program  
OECD: Organisation for Economic Co-operation and Development  
OSHA: Occupational Safety and Health Administration  
PA: Pennsylvania  
PEL: Permissible exposure limit  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
RCRA: Resource Conservation and Recovery Act  
RTECS: Registry of Toxic Effects of Chemical Substances  
SARA: Superfund Amendments and Reauthorization Act  
STEL: Short Term Exposure Limit  
TDG: Canadian Transportation of Dangerous Goods Act & Regulations  
TLV: Threshold Limit Values  
TPQ: Threshold Planning Quantity  
TSCA: Toxic Substance Control Act  
TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Identification System

**References:**

Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2015 (Chempendium, RTECs, HSDB, INCHEM).  
OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015  
European Chemicals Agency, Classification Legislation, 2015 Material Safety Data Sheet from manufacturer.

Preparation Date (mm/dd/yyyy): 08/07/2018

**Other special considerations for handling**

: Provide adequate information, instruction and training for operators.




Dampney Company, Inc.  
85 Paris Street  
Everett, Massachusetts, U.S.A.02149  
Email: sales@dampney.com  
Telephone: (617) 389 2805

Thurmalox 70C  
SDS Preparation Date (mm/dd/yyyy): 08/07/2018

Page 11 of 11

### SAFETY DATA SHEET

<p>Dampney Company, Inc. 85 Paris Street Everett MA 02149 U.S.A Telephone: (617) 389-2805 Please direct all inquiries to Dampney Company.</p>	
---	--

#### DISCLAIMER

This Safety Data Sheet was prepared by Dampney Company, Inc and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Dampney Company, Inc expressly disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Dampney Company, Inc.

END OF DOCUMENT