

Endcor 560C SDS Preparation Date (mm/dd/yyyy) 05/04/2021

Page 1 of 9

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label:

Endcor 560C

Product Code(s) : 560C

Recommended use of the chemical and restrictions on use

: Alkyd Primer for new construction and maintenance applications

Use pattern: Professional Use Only Recommended restrictions: None Known.

Chemical family : Mixture.

Name, address, and telephone number of the manufacturer:

Dampney Company, Inc.

85 Paris Street

Everett, Massachusetts, U.S.A. 02149

Email: sales@dampney.com

Supplier's Telephone # : (617) 389-2805

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887(Outside U.S.).

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Gray liquid. Solvent odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification:

Flammable Liquids - Category 2 Skin Irritation - Category 2 Acute toxicity (Oral) – Category 4 Eye Damage/Irritation - Category 2A Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory)

Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory)
Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects

Label elements

Hazard pictogram(s)



Signal Word

Warning.

Hazard statement(s)

Flammable liquid and vapour. Causes skin irritation.

Causes serious eye irritation.

Harmful if swallowed.

May cause respiratory irritation.

May cause drowsiness and dizziness.

Precautionary statement(s)

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing vapors or mists.

Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear protective gloves/clothing and eye/face protection.

Do not not drink or ample with using this product

Do not eat, drink or smoke with using this product.



Telephone: (617) 389 2805

Endcor 560C SDS Preparation Date (mm/dd/yyyy) 05/04/2021

Page 2 of 9

SAFETY DATA SHEET

Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF SWALLOWED: Call a POISOON CENTER or doctor/physician if you feel unwell. Rinse mouth.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use alcohol-resistant foam, carbon dioxide or dry chemical to extinguish.

Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

No OSHA defined hazard classes.

Other hazards which do not result in classification: May be sensitive to static discharge. Burning produces obnoxious and toxic fumes. Ingestion can cause gastrointestinal irritation, nausea, and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS#	Concentration (% by weight)
Methyl amyl ketone	110-43-0	23.51
Methyl propyl ketone	107-87-9	5.40
Carbon Black (amorphous)	1333-86-4	0.46

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion:

IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact:

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.

Most important symptoms and effects, both acute and delayed

May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. May cause drowsiness and dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Causes skin irritation. Symptoms may include redness, itching and swelling. Causes eye irritation. Symptoms may include tearing, redness and discomfort. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically. This product is a CNS depressant.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Unsuitable extinguishing media: Do not use water jet, as this may spread burning material.



Telephone: (617) 389 2805

Endcor 560C SDS Preparation Date (mm/dd/yyyy) 05/04/2021

Page 3 of 9

SAFETY DATA SHEET

Special hazards arising from the substance or mixture / Conditions of flammability

: Flammable liquid and vapour. Keep away from heat and flame. This product will accumulate static charge by flow, splashing or agitation. Vapors may travel considerable distance to a source of ignition and flash back. Vapours are heavier than air and collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

Flammable Liquids - Category 3

Hazardous combustion products:

Carbon oxides; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures:

Move containers from fire area if safe to do so. Use water spray to cool unopened containers. Avoid spreading burning liquid with water spray used for cooling purposes. Do not allow run-off from fire fighting to enter drains or water courses. Prevent fire extinguishing water from contaminating surface water or the ground water system. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapour or mist. Restrict access to area until completion of clean-up. Remove all sources of ignition. All persons dealing with the clean-up should wear the appropriate personal protective equipment. For personal protection see section 8.

Environmental precautions:

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up:

Special spill response procedures

Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Contaminated absorbent material may pose the same hazards as the spilled product. Pick up and transfer to properly labeled containers. Contact the proper local

In case of a transportation accident, in the United States contact CHEMTREC at

1-800-424-9300 or International at 1-703-527-3887. EPA/CERCLA Reportable quantity (RQ): None.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Keep away from heat and flame. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Bond and ground transfer containers and equipment. Use explosion-proof electrical and ventilating equipment. Use non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection. Avoid breathing vapour or mist. Do not ingest. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials. Encourage good housekeeping and personal hygiene.

Conditions for safe storage

Store in well-ventilated place. Keep cool. Store locked up, Keep container tightly closed. Store away from incompatibles and out of direct sunlight. Take measures to prevent the build-up of electrostatic charge. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials

Strong oxidizers, acids and bases.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

Chemical Name	ACGIH	TLV	OSHA	PEL	
	TWA	STEL	PEL	STEL	
Methyl amyl ketone	50 ppm	N/Av	100 ppm ; 465 mg/m³	N/Av	



Endcor 560C

SDS Preparation Date (mm/dd/yyyy) 05/04/2021

Page 4 of 9

SAFETY DATA SHEET

Methyl propyl ketone	N/Av	N/Av	200 ppm ; 700 mg/m ³	150 ppm
Carbon Black (amorphous)	N/Av	N/Av	N/Av	N/Av

Exposure controls

Ventilation and engineering measures

: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

: If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection

: Wear protective gloves. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection

: Chemical splash goggles are recommended.

Other protective equipment

: Ensure that eyewash stations and safety showers are close to the workstation location.

Other equipment may be required depending on workplace standards.

General hygiene considerations

: Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Gray
Odour : Solvent odor.
Ph : N/Av
Melting/Freezing point : N/Av
Initial boiling point and boiling range : 220.0° - 308.0°F

Flash point : 49.0°F
Flashpoint (Method) : Closed cup

Evaporation rate (BuAe = 1) : .242 times slower than n-Butyl acetate

Lower flammable limit (% by vol.)

Upper flammable limit (% by vol.)

Oxidizing properties

Explosive properties

Vapour pressure

Vapour density

Relative density / Specific gravity

: 1.1%

None known.

Not explosive

N/Av

Heavier than air

Relative density / Specific gravity : 1.33812
Weight per gallon : 11.1 lb/gal
Auto-ignition temperature : N/Av
Volatiles (% by weight) : 31.0%
Volatiles (% by volume) : 51.0%
Volatile organic Compounds (VOC's) : 3.47 lbs/gal

Other physical/chemical comments : None reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: Not normally reactive.

Chemical stability

: Stable under normal conditions.

Possibility of hazardous reactions

: Hazardous polymerization does not occur. May be sensitive to static discharge.

Conditions to avoid



Endcor 560C SDS Preparation Date (mm/dd/yyyy) 05/04/2021

Page 5 of 9

SAFETY DATA SHEET

: Keep away from heat, sparks and flame. Take precautionary measures against static discharge. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials.

Incompatible materials: Strong oxidizers, acids and bases.

Hazardous decomposition products

None reported by the manufacturer. In the event of fire the following can be released: Carbon oxides; other unidentified organic compounds.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES Routes of entry skin & eye YES Routes of entry Ingestion YES Routes of exposure skin absorption : NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: May cause respiratory irritation. Symptoms may include sore throat, running nose and shortness of breath. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Causes symptoms similar to those listed for inhalation.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Skin Irritation - Category 2 Causes skin irritation. Symptoms may include mild redness and swelling.

Sign and symptoms eyes

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Eye Damage/Irritation - Category 2B Causes eye irritation. Symptoms may include tearing, redness and discomfort.

Potential Chronic Health Effects

Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Mutagenicity : Not expected to be mutagenic in humans.

: No components present at greater than 0.1% are considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

Reproductive effects & Teratogenicity : This product is not expected to cause reproductive or developmental effects.

Sensitization to material : Not expected to be a skin or respiratory sensitizer.

Specific target organ effects: Eyes, skin, respiratory system, digestive system, central nervous system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory) May cause respiratory

irritation.

Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects May cause drowsiness and dizziness. Not classified as specific target organ toxicity-repeated exposure.

Not classified as a specific target organ toxicity - repeated exposure.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials : None reported by the manufacturer.

Toxicological data:

There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data. See below for individual ingredient acute toxicity data.

LC50(4hr)	LD50		
Chemical name	inh, rat	(Oral, rat)	(Rabbit, dermal)



Telephone: (617) 389 2805

Endcor 560C

SDS Preparation Date (mm/dd/yyyy) 05/04/2021

Page 6 of 9

SAFETY DATA SHEET

Methyl amyl ketone	>16 mg/L	1,670 mg/kg	10,300 mg/kg
Methyl propyl ketone	25.5 mg/l	1,600 mg/kg	>20 ml/kg
Carbon Black (amorphous)	NOEL 1 mg/m3	>8,000 mg/kg	N/Av

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: Should not be released into the environment. See the following tables for the substance's ecotoxicity data.

Ecotoxicity data:

Ingredients	0401	Toxicity to Fish			
	CAS No	LC50 / 96h	NOEC / 21 day	M Factor	
Methyl amyl ketone	110-43-0	131 mg/L (Fathead minnow)	N/Av	none	
Methyl propyl ketone	107-87-9	1,240 mg/L (Fathead minnow)	N/Av	None	
Carbon Black (amorphous)	1333-86-4	>1,000 mg/L (zebrafish)	N/Av	N/Av	

Ingredients	CACNA	Toxicity to Daphnia				
	CAS No	EC50 / 48h	NOEC / 21 day	M Factor		
Methyl amyl ketone	110-43-0	n/av	n/av	none		
Methyl propyl ketone	107-87-9	110 mg/L (waterflea) 24 hr	N/Av	none		
Carbon Black (amorphous)	1333-86-4	>5,000 mg/L (waterflea) 24	N/Av	N/Av		

Ingredients	CAS No	Toxicity to Algae			
	OAO NO	EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor	
Methyl amyl ketone	110-43-0	75.5 mg/L (Green algae)	N/Av	none	
Methyl propyl ketone	107-87-9	150 mg/L (Green algae)	N/Av	none	
Carbon Black (amorphous)	1333-86-4	>10,000 mg/L	N/Av	none	

Persistence and degradability

: No data is available on the product itself.

Bioaccumulation potential: No data is available on the product itself.

Components	emponents Partition coefficient n-octanol/water (log Kow)	
Methyl amyl ketone	1.98	1.98
Methyl propyl ketone	N/Av	N/Av
Carbon Black (amorphous)	N/Ap	N/Ap

Mobility in soil

: No data is available on the product itself.

Other Adverse Environmental effects:

None known or reported by the manufacturer.



Endcor 560C SDS Preparation Date (mm/dd/yyyy) 05/04/2021

Page 7 of 9

SAFETY DATA SHEET

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

Methods of Disposal RCRA

- : Dispose in accordance with all applicable regulations.
- : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1263	PAINT	3	II	3
Additional information		ed as a limited quantity the maximum net capacity specifie gings may be increased to 5L (1.3 gallons) 172.102(C)(1)(1			
TDG	UN1263	PAINT	3	II	3
Additional information	May be shipped 30 kg gross ma	d as Limited Quantity when transported in containers no lar ss. ERG #128	ger than 5.0 Lit	res; in pack	ages not exceeding
IMDG	UN1263	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid laquer base)	3	II	3
Additional information		d as a Limited Quantity when transported in containers no light (66 pounds) gross mass.	arger than 5 L	(1.3 gallons); in packages not
ICAO/IATA Additional	UN1263	Paint	3	II	₹ <u>₩</u> 3
information	Refer to ICAO/I	ATA packing instruction.			

Special precautions for user

: Keep away from heat, sparks and open flame. - No smoking.

Environmental hazards: See ECOLOGICAL INFORMATION, Section 12.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

Ingredients CA		CAC # TSCA Repor		SARA TITLE III: Sec. 302, Extremely	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
	CAS#	CAS # Inventory		Hazardous Substance, 40 CFR 355:	Toxic Chemical	de minimus Concentration
Methyl amyl ketone	110-43-0	Yes	N/Ap	N/Av	No	N/Ap
Methyl propyl ketone	107-87-9	Yes	N/Ap	N/Av	No	N/Ap



Telephone: (617) 389 2805

Endcor 560C

SDS Preparation Date (mm/dd/yyyy) 05/04/2021

Page 8 of 9

SAFETY DATA SHEET

Carbon Black (amorphous) 1333-86-4	Yes	N/Ap	N/Av	No	N/Ap	l
------------------------------------	-----	------	------	----	------	---

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients	CAS#	California	State "Right to Know" Lists						
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Methyl amyl ketone	110-43-0	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Methyl propyl ketone	107-87-9	No	N/Ap	N/Av	N/Av	N/Av	N/Av	N/Av	N/Av
Carbon Black (amorphous)	1333-86-4	No	N/Ap	No	Yes	No	Yes	Yes	No

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL). WHMIS Classification: See Section 2.

International Information:

Components listed below are present on the following International Inventory list:

Ingredients	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Methyl amyl ketone	110-43-0	203-767-1	Present	Present	Not listed	Not listed	Present	Not listed
Methyl propyl ketone	107-87-9	203-528-1	Present	Present	(2)-542	KE-28009	Present	HSR001046
Carbon Black (amorphous)	1333-86-4	215-609-9	Present	Present	(10)-3074;(5)- 3328	KE-04682	Present	HSR002801

SECTION 16. OTHER INFORMATION

Legend:

ACGIH: American Conference of Governmental Industrial Hygienists

AICS: Australian Inventory of Chemical Substances

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980

CFR: Code of Federal Regulations CSA: Canadian Standards Association DOT: Department of Transportation EC50: Effective Concentration 50%.

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS: Existing and New Chemical Substances EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer IECSC: Inventory of Existing Chemical Substances IMDG: International Maritime Dangerous Goods

Inh: Inhalation

KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List

LC: Lethal Concentration LD: Lethal Dose N/Ap: Not Applicable

N/Av: Not Available



Endcor 560C SDS Preparation Date (mm/dd/yyyy) 05/04/2021

Page 9 of 9

SAFETY DATA SHEET

NFPA: National Fire Protection Association

NJ: New Jersey

NIOSH: National Institute of Occupational Safety and Health

NOEC: No observable effect concentration NTP: National Toxicology Program

OECD: Organisation for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PA: Pennsylvania

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

RCRA: Resource Conservation and Recovery Act RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TPQ: Threshold Planning Quantity TSCA: Toxic Substance Control Act TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

References

Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2015 (Chempendium, RTECs, HSDB, INCHEM). OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015

European Chemicals Agency, Classification Legislation, 2015 Material Safety Data Sheet from manufacturer.

Preparation Date (mm/dd/yyyy): 05/04/2021

Other special considerations for handling: Provide adequate information, instruction and training for operators.

Dampney Company, Inc. 85 Paris Street Everett MA 02149 U.S.A Telephone: (617) 389-2805



DISCLAIMER

This Safety Data Sheet was prepared by Dampney Company, Inc. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Dampney Company, Inc expressly disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Dampney Company, Inc.

END OF DOCUMENT