



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 230
SDS Preparation Date (mm/dd/yyyy): 02/03/2025

Page 1 of 9

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label: Thurmalox White

Product Code(s): 230

Recommended use of the chemical and restrictions on use: High Temperature Coating

Use pattern: Professional Use Only

Recommended restrictions: None Known.

Chemical family: Mixture.

Name, address, and telephone number of the manufacturer:

Dampney Company, Inc.

85 Paris Street

Everett, Massachusetts, U.S.A. 02149

Email: sales@dampney.com

Supplier's Telephone: (617) 389-2805

24 Hr. Emergency Tel: Chemtrec 1-800-424-9300 (Within North America).

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

White liquid. Solvent odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Flammable Liquid - Category 3

Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory)

Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects

Specific Target Organ Toxicity, Repeated Exposure - Category 2 (CNS)

Skin Irritation - Category 2

Carcinogen - Category 2

Reproductive Toxicity - Category 2

Label elements

Hazard pictogram(s)

GHS-02 Flame

GHS-07 Exclamation Mark

GHS-08 Health Hazard



Signal Word:

DANGER!

Hazard statement(s)

Flammable liquid and vapor. May cause respiratory irritation.

May cause drowsiness and dizziness.

May cause damage to organs through prolonged or repeated exposure. Causes skin irritation.

Suspected of causing cancer.

Suspected of damaging the unborn child.

Precautionary statement(s)

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe vapours or spray mist.

Use only outdoors or in a well-ventilated area. Wash thoroughly after handling.

Wear protective gloves/clothing and eye/face protection.

Response

If exposed or concerned: Get medical attention/advice.



Thurmalox 230
SDS Preparation Date (mm/dd/yyyy): 02/03/2025

Page 2 of 9

SAFETY DATA SHEET

If on skin (or hair): Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.
In case of fire: Use alcohol-resistant foam, carbon dioxide, or dry chemical to extinguish.

Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

No OSHA defined hazard classes.

Other hazards which do not result in classification: Burning produces obnoxious and toxic fumes. Direct eye contact may cause slight or mild, transient irritation. Ingestion can cause gastrointestinal irritation, nausea, and diarrhea.
Prolonged or repeated contact may cause drying, cracking, and defatting of the skin.

Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS #	Concentration (% by weight)
Xylene	1330-20-7	30.72
P-Chlorobenzotrifluoride	98-56-6	20.42
Ethylbenzene	100-41-4	5.80
Toluene	108-88-3	2.74
n-Butyl Alcohol	71-35-3	2.13

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion: IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. Material is an aspiration hazard. Guard against aspiration into lungs by having the individual turn on their left side. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Eye contact: In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.

Most important symptoms and effects, both acute and delayed: May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. May cause drowsiness and dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness, and other central nervous system effects. Causes skin irritation. Symptoms may include redness, itching and swelling. Direct eye contact may cause slight or mild, transient irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Suspected of causing cancer.

Indication of any immediate medical attention and special treatment needed: Treat symptomatically. This product is a CNS depressant.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.



SAFETY DATA SHEET

Unsuitable extinguishing media: Do not use water jet, as this may spread burning material.

Special hazards arising from the substance or mixture / Conditions of flammability: Combustible liquid and vapour. Keep away from heat and flame. This product will accumulate static charge by flow, splashing or agitation. Vapors may travel considerable distance to a source of ignition and flash back. Vapours are heavier than air and collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106): Flammable Liquids - Category 3

Hazardous combustion products: Carbon oxides; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures: Move containers from fire area if safe to do so. Use water spray to cool unopened containers. Avoid spreading burning liquid with water spray used for cooling purposes. Do not allow run-off from fire fighting to enter drains or water courses. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapour or mist. Restrict access to area until completion of clean-up. Remove all sources of ignition. All persons dealing with the clean-up should wear the appropriate personal protective equipment. For personal protection see section 8.

Environmental precautions: Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Contaminated absorbent material may pose the same hazards as the spilled product. Pick up and transfer to properly labeled containers. Contact the proper local authorities.

Special spill response procedures: In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat and flame. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Bond and ground transfer containers and equipment. Use explosion-proof electrical and ventilating equipment. Use non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection. Avoid breathing vapour or mist. Do not ingest. Avoid contact with skin, eyes, and clothing. Avoid contact with incompatible materials. Encourage good housekeeping and personal hygiene.

Conditions for safe storage: Store in well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Store away from incompatibles and out of direct sunlight. Take measures to prevent the buildup of electrostatic charge. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials: Strong oxidizers, acids, and bases.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

Chemical Name	OSHA TWA	OSHA PEL	OSHA STEL
Xylene	100 ppm	100 ppm (435 mg/m ³)	n/a
p-Chlorobenzotrifluoride	n/a	n/a	n/a



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 230
SDS Preparation Date (mm/dd/yyyy): 02/03/2025

Page 4 of 9

SAFETY DATA SHEET

Ethylbenzene	20 ppm	100 ppm (435 mg/m ³)	n/a
Toluene	20 ppm	200 ppm	300 ppm (Ceiling)
n-Butyl alcohol	20 ppm	100 ppm (300 mg/m ³)	n/a

Exposure controls

Ventilation and engineering measures: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection: If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection: Wear protective gloves. Where extensive exposure to product is possible, use resistant coveralls, apron, and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection: Chemical splash goggles are recommended.

Other protective equipment: Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations: Avoid breathing vapour or mist. Avoid contact with skin, eyes, and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking, or use of toilet facilities. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Odour	: White liquid. Solvent odor.
Odour threshold		: N/A
pH		: N/A
Melting/Freezing point		: N/A
Boiling range		: 275°F – 290°F
Flash point		: 80°F – 109°F
Lower flammable limit (% by vol.)		: 1.0
Upper flammable limit (% by vol.)		: 11.2
Evaporation rate (BuAe = 1)		: 0.452 times slower than n-Butyl Acetate.
Vapour pressure	Vapour density	: Heavier than air
% Volatile by weight		: 63.0%
% Volatile by volume		: 79.0%
Relative density / Specific gravity		: 1.25818
Weight per gallon		: 10.5 lbs
VOC		: 5.38 lbs / gal

SECTION 10. STABILITY AND REACTIVITY

Incompatibility: Avoid contact with strong oxidizing agents, acids, or bases.

Conditions to avoid: Keep away from heat, sparks, and flame. Take precautionary measures against static discharge. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials.

Hazardous decomposition products: Carbon monoxide and unidentified organics may be formed.

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation: May cause respiratory irritation. Symptoms may include sore throat, running nose and shortness of breath. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties, and

SAFETY DATA SHEET

unconsciousness.

Sign and symptoms ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Causes symptoms similar to those listed for inhalation.

Sign and symptoms skin: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Skin Irritation - Category 2
Causes skin irritation. Symptoms may include mild redness and swelling.

Sign and symptoms eyes: Direct eye contact may cause slight or mild, transient irritation.

Potential Chronic Health Effects: Prolonged or repeated contact may cause drying, cracking, and defatting of the skin.

Mutagenicity: Not expected to be mutagenic in humans.

Carcinogenicity: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Carcinogenicity - Category 2 Suspected of causing cancer. Contains Ethylbenzene. Ethylbenzene is classified as carcinogenic by IARC (Group 2B) and ACGIH (Category A3).

Reproductive effects & Teratogenicity: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Reproductive Toxicity - Category 2 Suspected of damaging the unborn child.

Sensitization to material: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects: Eyes, skin, respiratory system, digestive system, central nervous system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification:

Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory) May cause respiratory irritation.

Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects May cause drowsiness and dizziness.

Specific Target Organ Toxicity, Repeated Exposure - Category 2 May cause damage to organs through prolonged or repeated exposure.

Contains Toluene.

Toluene may cause damage to the brain and nervous system through prolonged or repeated exposure, if inhaled.

Medical conditions aggravated by overexposure: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials: None reported by the manufacturer.

Toxicological data: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data. See below for individual ingredient acute toxicity data.

Chemical name	LC50(4hr) Inhalation rat	LD50	
		(Oral, rat)	(Rabbit, dermal)
Xylene	6350 ppm (27.6 mg/L) (vapours)	3253 mg/kg	12 180 mg/kg
p-Chlorobenzotrifluoride	33 mg/L 4 h	13 g/kg	N/Av
Ethylbenzene	4000 ppm (17.4 mg/L) (vapour)	3500 mg/kg	15 380 mg/kg
Toluene	7585 ppm (28.1 mg/L) (vapour)	5580 mg/kg	12 125 mg/kg
n-Butyl alcohol	8000 ppm (24.3 mg/L) (vapour)	790 - 4360 mg/kg	3402 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: Contains material that may be harmful in the environment. Should not be released into the environment. See the following tables for the substance's ecotoxicity data.

Ecotoxicity data:

Ingredients	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Xylene	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.
p-Chlorobenzotrifluoride	98-56-6	11.5-15.8 mg/L Lepomis macrochirus	N/Av	None.
Ethylbenzene	100-41-4	4.2 mg/L (Rainbow trout)	1.13 mg/L/30 days	None.
Toluene	108-88-3	5.4 mg/L (pink salmon)	1.4 - 4.0 mg/L	None.
n-Butyl alcohol	71-36-3	1376 mg/L (Fathead minnow)	N/Av	None.



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 230
SDS Preparation Date (mm/dd/yyyy): 02/03/2025

Page 6 of 9

SAFETY DATA SHEET

Ingredients	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Xylene	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.
p-Chlorobenzotrifluoride	98-56-6	N/Av	N/Av	None.
Ethylbenzene	100-41-4	1.81 mg/L (Daphnia magna)	N/Av	None.
Toluene	108-88-3	3.78 mg/L Ceriodaphnia (water flea)	0.53 - 1 mg/L	None.
n-Butyl alcohol	71-36-3	1328 mg/L (Daphnia magna)	4.1 mg/L	None.

Ingredients	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Xylene	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.
p-Chlorobenzotrifluoride	98-56-6	N/Av	N/Av	None.
Ethylbenzene	100-41-4	3.6 mg/L/96hr (Green algae)	3.4 mg/L/96hr	None.
Toluene	108-88-3	N/Av	10 mg/L/72hr (Green algae)	None.
n-Butyl alcohol	71-36-3	225 mg/L/96hr (Green algae)	129 mg/L/96hr	None.

Persistence and degradability: No data is available on the product itself.

Bioaccumulation potential: No data is available on the product itself.

Components	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
Xylene	3.12 - 3.2	0.6 - 15
p-Chlorobenzotrifluoride	3.7 at 25 °C	N/Av
Ethylbenzene	3.15	15 species: fish
Toluene	2.73	N/Av
n-Butyl alcohol	0.88	0.64 species: freshwater fish

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

Methods of Disposal: Dispose in accordance with all applicable regulations.

RCRA: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state, and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1263	Paint	3	III	
Additional information	When transported as a limited quantity the maximum net capacity specified in 173.150(b)(2) of the subchapter 49CFR for inner packagings may be increased to 5L (1.3 gallons) 172.102(C)(1) (149) special provision 149.				
TDG	UN1263	Paint	3	III	



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 230
SDS Preparation Date (mm/dd/yyyy): 02/03/2025

Page 7 of 9

SAFETY DATA SHEET

Additional information	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				
IMDG	UN1263	PAINT	3	III	
Additional information	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				
ICAO/IATA	UN1263	Paint	3	III	
Additional information	Refer to ICAO/IATA Packing Instruction.				

Special precautions for user: Keep away from heat, sparks, and open flame. - No smoking.

Environmental hazards: See ECOLOGICAL INFORMATION, Section 12.

SECTION 15 - REGULATORY INFORMATION

US Federal Information: Components listed below are present on the following U.S. Federal chemical lists:

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity (RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Xylene	1330-20-7	Yes	100 lb/ 45.4 kg	None.	Yes	1%
p-Chlorobenzotrifluoride	98-56-6	Yes	N/Ap	N/Av	No	NS
Ethylbenzene	100-41-4	Yes	1000 lb/ 454 kg	None.	Yes	0.1%
Toluene	108-88-3	Yes	1000 lb/ 454 kg	None.	Yes	1%
n-Butyl alcohol	71-36-3	Yes	5000 lb/ 2270 kg	None.	Yes	1%

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws: The following chemicals are specifically listed by individual States:

Ingredients	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Xylene	1330-20-7	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
p-Chlorobenzotrifluoride	98-56-6	No	N/Ap	No	No	No	No	No	No
Ethylbenzene	100-41-4	Yes	Cancer	Yes	Yes	Yes	Yes	Yes	Yes
Toluene	108-88-3	No	Developmental	Yes	Yes	Yes	Yes	Yes	Yes
n-Butyl alcohol	71-36-3	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information: Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS Classification: See Section 2.

International Information: Components listed below are present on the following International Inventory list:



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 230
SDS Preparation Date (mm/dd/yyyy): 02/03/2025

Page 8 of 9

SAFETY DATA SHEET

Ingredients	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Xylene	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983
p-Chlorobenzotrifluoride	98-56-6	202-681-1	Present	Present	(3)-53	KE-05928	Present	HSR005269 (dilution)
Ethylbenzene	100-41-4	202-849-4	Present	Present	(3)-60; (3)-28	KE-13532	Present	HSR001151
Toluene	108-88-3	203-625-9	Present	Present	(3)-2	KE-33936	Present	HSR001227
n-Butyl alcohol	71-36-3	200-751-6	Present	Present	(2)-3049	KE-03867	Present	HSR001096

SECTION 16. OTHER INFORMATION

Legend: ACGIH: American Conference of Governmental Industrial Hygienists

AICS: Australian Inventory of Chemical Substances

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980

CFR: Code of Federal Regulations

CSA: Canadian Standards Association

DOT: Department of Transportation

EC50: Effective Concentration 50%.

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS: Existing and New Chemical Substances

EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System

HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

IECSC: Inventory of Existing Chemical Substances

IMDG: International Maritime Dangerous Goods

Inh: Inhalation

KECI: Korean Existing Chemicals Inventory

KECL: Korean Existing Chemicals List

LC: Lethal Concentration

LD: Lethal Dose

N/Ap: Not Applicable

N/Av: Not Available

NFPA: National Fire Protection Association

NJ: New Jersey

NIOSH: National Institute of Occupational Safety and Health

NOEC: No observable effect concentration

NTP: National Toxicology Program

OECD: Organization for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PA: Pennsylvania

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

RCRA: Resource Conservation and Recovery Act

RTECS: Registry of Toxic Effects of Chemical Substances

SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values

TPQ: Threshold Planning Quantity

TSCA: Toxic Substance Control Act

TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

References:

Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2015 (Chempendium, RTECs, HSDB, INCHEM).

OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015

European Chemicals Agency, Classification Legislation, 2015 Material Safety Data Sheet from manufacturers.



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 230
SDS Preparation Date (mm/dd/yyyy): 02/03/2025

Page 9 of 9

SAFETY DATA SHEET

Preparation Date (mm/dd/yyyy): 02/03/2025

Other special considerations for handling: Provide adequate information, instruction, and training for operators.

Dampney Company, Inc.
85 Paris Street
Everett MA 02149 U.S.A
Telephone: (617) 389-2805
Please direct all inquiries to Dampney Company.



DISCLAIMER

This Safety Data Sheet was prepared by Dampney Company, Inc. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Dampney Company, Inc expressly disclaims all expressed or implied warranties and assumes no responsibility for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission Dampney Company, Inc.

END OF DOCUMENT