



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 1 of 14

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Thurmalox 242C-02**

Product Code(s)

: 242C-02

Recommended use of the chemical and restrictions on use

: Coating 1400-1600F VOC
Use pattern: Professional Use Only
Recommended restrictions: None Known.

Chemical family

: Mixture.

Name, address, and telephone number
of the supplier:

Dampney Company, Inc.

85 Paris Street
Everett, Massachusetts, U.S.A.
02149

Email: sales@dampney.com

Supplier's Telephone #

: (617) 389-2805

24 Hr. Emergency Tel #

: Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887
(Outside U.S.).

Name, address, and telephone number of
the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Black liquid. Aromatic odour.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification:

Flammable Liquids - Category 2

Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory)

Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects

Specific Target Organ Toxicity, Repeated Exposure. - Category 1 (Central nervous system)

Skin Irritation - Category 2

Serious eye damage/eye irritation - Category 2A

Reproductive Toxicity - Category 2

Label elements

Hazard pictogram(s)



Signal Word

DANGER!



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 2 of 14

SAFETY DATA SHEET

Hazard statement(s)

Highly flammable liquid and vapor.
May cause respiratory irritation.
May cause drowsiness and dizziness.
Causes damage to organs through prolonged or repeated exposure by inhalation.
Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging the unborn child.

Precautionary statement(s)

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing vapors or mists.
Use only outdoors or in a well-ventilated area.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves/clothing and eye/face protection.

If exposed or concerned: Get medical attention/advice.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTRE or doctor/physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists: get medical advice/attention.
In case of fire: Use alcohol-resistant foam, carbon dioxide or dry chemical to extinguish.

Store in a well-ventilated place.
Keep container tightly closed.
Keep cool.
Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

No OSHA defined hazard classes.

Other hazards which do not result in classification:

May be sensitive to static discharge. Burning produces obnoxious and toxic fumes.

Direct eye contact may cause slight or mild, transient irritation. Ingestion can cause gastrointestinal irritation, nausea, and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 3 of 14

SAFETY DATA SHEET

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Acetone	2-Propanone Methyl ketone	67-64-1	10.0 - 15.0
p-Chlorobenzotrifluoride	Dimethylbenzene Methyltoluene Xylol	98-56-6	5.0 - 10.0
Chromium and compounds	Elemental chromium	7440-47-3	1.0 - 5.0
Manganese (and compounds)	Elemental manganese	7439-96-5	1.0 - 5.0
n-Butyl alcohol	n-Butanol 1-Hydroxybutane	71-36-3	1.0 - 5.0
Xylene	Dimethylbenzene Methyltoluene Xylol	1330-20-7	1.0 - 5.0
n-Butyl-acetate	1-Acetoxybutane Butyl ethanoate	123-86-4	1.0 - 5.0
Toluene	Methylbenzene Phenylmethane	108-88-3	1.0 - 5.0
Petroleum Distillates	Mineral spirits White spirit	8052-41-3	1.0 - 5.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. Material is an aspiration hazard. Guard against aspiration into lungs by having the individual turn on their left side. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.
- Skin contact* : IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER or doctor/physician if you feel unwell.
- Eye contact* : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.

Most important symptoms and effects, both acute and delayed

- : May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. May cause drowsiness and dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Causes skin irritation. Symptoms may include redness, itching and swelling. Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis. Suspected of damaging fertility or the unborn child. Causes damage to the peripheral nervous system through prolonged or repeated exposure if inhaled. Manganese can attack the central nervous system, causing symptom's similar to Parkinson's Disease.

Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically. This product is a CNS depressant.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 4 of 14

SAFETY DATA SHEET

Suitable extinguishing media

: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media

: Do not use water jet, as this may spread burning material.

Special hazards arising from the substance or mixture / Conditions of flammability

: Flammable liquid and vapour. This product will accumulate static charge by flow, splashing or agitation. Vapors may travel considerable distance to a source of ignition and flash back. Vapours are heavier than air and collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

: Flammable Liquids - Category 2

Hazardous combustion products

: Carbon oxides ; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures

: Move containers from fire area if safe to do so. Use water spray to cool unopened containers. Avoid spreading burning liquid with water spray used for cooling purposes. Do not allow run-off from fire fighting to enter drains or water courses. Prevent fire extinguishing water from contaminating surface water or the ground water system. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapour or mist. Restrict access to area until completion of clean-up. Remove all sources of ignition. All persons dealing with the clean-up should wear the appropriate personal protective equipment. For personal protection see section 8.

Environmental precautions

: Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up

: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Contaminated absorbent material may pose the same hazards as the spilled product. Pick up and transfer to properly labeled containers. Contact the proper local authorities.



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 5 of 14

SAFETY DATA SHEET

Special spill response procedures

- : In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887.

EPA/CERCLA Reportable quantity (RQ):

- Xylene (100 lbs / 45.4 kg)
- Toluene (1000 lbs / 454 kg)
- chromium (5000 lbs / 2270 kg)
- n-Butyl alcohol (5000 lbs / 2270 kg)
- n-Butyl acetate (5000 lbs / 2270 kg)
- Acetone (5000 lbs / 2270 kg)

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat and flame. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Bond and ground transfer containers and equipment. Use explosion-proof electrical and ventilating equipment. Use non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection. Avoid breathing vapour or mist. Do not ingest. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials.

Conditions for safe storage

- : Store in well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Store away from incompatibles and out of direct sunlight. Take measures to prevent the build up of electrostatic charge. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials

- : Strong oxidizers, acids and bases.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

Chemical Name	ACGIH TLV		OSHA PEL	
	TWA	STEL	PEL	STEL
Acetone	250 ppm	500 ppm	1000 ppm (2400 mg/m ³)	N/Av
p-Chlorobenzotrifluoride	N/Av	N/Av	N/Av	N/Av
Chromium and compounds	0.5 mg/m ³ (as 'metal & Cr III compounds')	N/Av	1 mg/m ³ (metal & insoluble salts)	N/Av
Manganese (and compounds)	0.02 mg/m ³ (respirable); 0.1 mg/m ³ (inhalable)	N/Av	5 mg/m ³ (fume) (Ceiling)	N/Av
n-Butyl alcohol	20 ppm	N/Av	100 ppm (300 mg/m ³)	N/Av
Xylene	100 ppm	150 ppm	100 ppm (435 mg/m ³)	N/Av
n-Butyl-acetate	150 ppm	200 ppm	150 ppm (710 mg/m ³)	N/Av
Toluene	20 ppm	N/Av	200 ppm	300 ppm (Ceiling)
Petroleum Distillates	100 ppm	N/Av	500 ppm (2900 mg/m ³)	N/Av



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 6 of 14

SAFETY DATA SHEET

Exposure controls

Ventilation and engineering measures

: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

: If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection

: Wear protective gloves. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection

: Chemical splash goggles are recommended.

Other protective equipment

: Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations

: Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Black liquid.
Odour	: Aromatic.
Odour threshold	: N/Av
pH	: N/Av
Melting/Freezing point	: N/Av
Initial boiling point and boiling range	: 55 -202.2°C (131-396°F)
Flash point	: -20 - 46.1°C (-4-115°F)
Flashpoint (Method)	: Closed cup
Evaporation rate (BuAe = 1)	: 1.617 times faster than n-Butyl acetate
Flammability (solid, gas)	: N/Av
Lower flammable limit (% by vol.)	: N/Av
Upper flammable limit (% by vol.)	: N/Av
Oxidizing properties	: None known.
Explosive properties	: Not explosive
Vapour pressure	: N/Av
Vapour density	: >1
Relative density / Specific gravity	: 1.44816
Solubility in water	: N/Av
Other solubility(ies)	: N/Av
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution	: N/Av
Auto-ignition temperature	: N/Av



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 7 of 14

SAFETY DATA SHEET

Decomposition temperature : N/Av
Viscosity : 300 cSt at 40°C
Volatiles (% by weight) : 34.82%
Volatile organic Compounds (VOC's)
: 2.6lbs/gal
Absolute pressure of container
: N/Av
Flame projection length : N/Av
Other physical/chemical comments
: None reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions
: Hazardous polymerization does not occur. May be sensitive to static discharge.
Conditions to avoid : Keep away from heat, sparks and flame. Take precautionary measures against static discharge. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials.
Incompatible materials : Strong oxidizers, acids and bases.
Hazardous decomposition products
: See Section 5 (Fire Fighting Measures).

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption
: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: May cause respiratory irritation. Symptoms may include sore throat, running nose and shortness of breath. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Causes symptoms similar to those listed for inhalation.

Sign and symptoms skin

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Skin Irritation - Category 2 Causes skin irritation. Symptoms may include mild redness and swelling.

Sign and symptoms eyes

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Serious eye damage/eye irritation - Category 2A Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 8 of 14

SAFETY DATA SHEET

Potential Chronic Health Effects

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin. Chronic manganese exposures can lead to neurological problems such as apathy, drowsiness, weakness, spastic gait, paralysis, and other neurological problems resembling Parkinsonism. These symptoms can become progressive and permanent if not treated.

Mutagenicity

: Not expected to be mutagenic in humans.

Carcinogenicity

: No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:
 Reproductive Toxicity - Category 2 Suspected of damaging the unborn child.

Sensitization to material

: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

: Eyes, skin, respiratory system, digestive system, central nervous system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).
 Classification:

Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory) May cause respiratory irritation.

Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects May cause drowsiness and dizziness. Specific Target Organ Toxicity, Repeated Exposure.

Category 1 Causes damage to the peripheral nervous system through prolonged or repeated exposure if inhaled.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials

: None reported by the manufacturer.

Toxicological data

: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

Chemical name	LC₅₀(4hr)	LD₅₀	
	inh. rat	(Oral, rat)	(Rabbit, dermal)
Acetone	30 000 ppm (71 mg/L) (vapour)	5800 mg/kg	> 15 800 mg/kg
p-Chlorobenzotrifluoride	33 mg/L 4 h	13 g/kg	N/Av
Chromium and compounds	> 5.41 mg/L (dust)	> 3400 mg/kg (No mortality)	N/Av
Manganese (and compounds)	> 5.14 mg/L (dust) (No mortality)	> 2000 mg/kg (No mortality)	N/Av
n-Butyl alcohol	8000 ppm (24.3 mg/L) (vapour)	790 - 4360 mg/kg	3402 mg/kg
Xylene	6350 ppm (27.6 mg/L) (vapours)	3253 mg/kg	12 180 mg/kg
n-Butyl-acetate	> 6867 ppm (vapour) 1.802 mg/L (aerosol)	10 700 mg/kg	> 5000 mg/kg
Toluene	7585 ppm (28.1 mg/L) (vapour)	5580 mg/kg	12 125 mg/kg
Petroleum Distillates	> 5.5 mg/L (vapour)	> 5000 mg/kg	> 3000 mg/kg

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 9 of 14

SAFETY DATA SHEET

Ecotoxicity : Contains material that may be harmful in the environment. Should not be released into the environment. See the following tables for the substance's ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Acetone	67-64-1	6210 mg/L (Fathead minnow)	N/Av	None.
p-Chlorobenzotrifluoride	98-56-6	Lepomis macrochirus: 11.5 - 15.8 mg/L	N/Av	None.
Chromium and compounds	7440-47-3	33 - 71.9 mg/L (Guppy)	N/Av	None.
Manganese (and compounds)	7439-96-5	28 mg/L (Fathead minnow)	N/Av	None.
n-Butyl alcohol	71-36-3	1376 mg/L (Fathead minnow)	N/Av	None.
Xylene	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.
n-Butyl-acetate	123-86-4	18 mg/L (Fathead minnow)	N/Av	None.
Toluene	108-88-3	5.4 mg/L (pink salmon)	1.4 - 4.0 mg/L	None.
Petroleum Distillates	8052-41-3	2.1 - 4.2 mg/L (Bluegill sunfish)	N/Av	None.

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Acetone	67-64-1	15 800 mg/L (Daphnia magna)	1660 mg/L	None.
p-Chlorobenzotrifluoride	98-56-6	Daphnia magna: 3.68 mg/L	N/Av	None.
Chromium and compounds	7440-47-3	N/Av	N/Av	None.
Manganese (and compounds)	7439-96-5	40 mg/L (Daphnia magna)	N/Av	None.
n-Butyl alcohol	71-36-3	1328 mg/L (Daphnia magna)	4.1 mg/L	None.
Xylene	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.
n-Butyl-acetate	123-86-4	44 mg/L (Daphnia magna)	23 mg/L (Read-across)	None.
Toluene	108-88-3	3.78 mg/L Ceriodaphnia (water flea)	0.53 - 1 mg/L	None.
Petroleum Distillates	8052-41-3	0.42 - 2.3 mg/L (Daphnia magna)	0.1 - 0.37 mg/L	None.



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 10 of 14

SAFETY DATA SHEET

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Algae</u>		
		<u>EC50 / 96h or 72h</u>	<u>NOEC / 96h or 72h</u>	<u>M Factor</u>
Acetone	67-64-1	7000 mg/L/96hr (Green algae)	N/Av	None.
p-Chlorobenzotrifluoride	98-56-6	N/Av	N/Av	None.
Chromium and compounds	7440-47-3	N/Av	N/Av	None.
Manganese (and compounds)	7439-96-5	4.5 mg/L/72hr (Green algae)	2.5 mg/L/72hr	None.
n-Butyl alcohol	71-36-3	225 mg/L/96hr (Green algae)	129 mg/L/96hr	None.
Xylene	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.
n-Butyl-acetate	123-86-4	675 mg/L/72hr (Green algae)	200 mg/L/72hr	None.
Toluene	108-88-3	N/Av	10 mg/L/72hr (Green algae)	None.
Petroleum Distillates	8052-41-3	0.58 - 1.2 mg/L/72hr (Green algae) (Closed systems - low end; Open systems - high end)	0.16 mg/L/72hr	None.

Persistence and degradability

: No data is available on the product itself.

Bioaccumulation potential

: No data is available on the product itself.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Acetone (CAS 67-64-1)	0.24	0.69 species: fish
p-Chlorobenzotrifluoride (CAS 98-56-6)	3.7 at 25 °C	0.6 - 15
Chromium and compounds (CAS 7440-47-3)	N/Av	N/Av
Manganese (and compounds) (CAS 7439-96-5)	N/Av	N/Av
n-Butyl alcohol (CAS 71-36-3)	0.88	0.64 species: freshwater fish
Xylene (CAS 1330-20-7)	3.12 - 3.2	0.6 - 15
n-Butyl-acetate (CAS 123-86-4)	2.3	15.3
Toluene (CAS 108-88-3)	2.73	90
Petroleum Distillates (CAS 8052-41-3)	3.16 - 7.06	N/Av

Mobility in soil

: No data is available on the product itself.

Other Adverse Environmental effects

: None known or reported by the manufacturer.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

Methods of Disposal

: Dispose in accordance with all applicable regulations.



Thurmalox 242C-02





SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 11 of 14

SAFETY DATA SHEET

RCRA : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1263	PAINT	3	II	
49CFR/DOT Additional information	When transported as a limited quantity the maximum net capacity specified in 173.150(b)(2) of the subchapter 49CFR for inner packagings may be increased to 5L (1.3 gallons) 172.102(C)(1)(149) special provision 149.				
TDG	UN1263	PAINT	3	II	
TDG Additional information	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass.				
IMDG	UN1263	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid laquer base)	3	II	
IMDG Additional information	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass.				
ICAO/IATA	UN1263	Paint	3	II	
ICAO/IATA Additional information	Refer to the appropriate Packing Instruction, prior to shipping this material.				

Special precautions for user : Keep away from heat, sparks and open flame. - No smoking.

Environmental hazards : See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 12 of 14

SAFETY DATA SHEET

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Acetone	67-64-1	Yes	5000 lb/ 2270 kg	None.	No	N/Ap
p-Chlorobenzotrifluoride	98-56-6	Yes	N/Ap	N/Av	No	NS
Chromium and compounds	7440-47-3	Yes	5000 lbs / 2270 kg	None.	Yes	1%
Manganese (and compounds)	7439-96-5	Yes	None.	None.	Yes	1%
n-Butyl alcohol	71-36-3	Yes	5000 lb/ 2270 kg	None.	Yes	1%
Xylene	1330-20-7	Yes	100 lb/ 45.4 kg	None.	Yes	1%
n-Butyl-acetate	123-86-4	Yes	5000 lb/ 2270 kg	None.	No	N/Ap
Toluene	108-88-3	Yes	1000 lb/ 454 kg	None.	Yes	1%
Petroleum Distillates	8052-41-3	Yes	None.	None.	No	N/Ap

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Acetone	67-64-1	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
p-Chlorobenzotrifluoride	98-56-6	No	N/Ap	No	No	No	No	No	No
Chromium and compounds	7440-47-3	Yes	Cancer; male; female; Developmental (applies only to hexavalent compounds)	Yes	Yes	Yes	Yes	Yes	Yes
Manganese (and compounds)	7439-96-5	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
n-Butyl alcohol	71-36-3	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Xylene	1330-20-7	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
n-Butyl-acetate	123-86-4	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Toluene	108-88-3	No	Developmental	Yes	Yes	Yes	Yes	Yes	Yes
Petroleum Distillates	8052-41-3	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS Classification: See Section 2.



Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 13 of 14

SAFETY DATA SHEET

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	<u>CAS #</u>	<u>European EINECS</u>	<u>Australia AICS</u>	<u>Philippines PICCS</u>	<u>Japan ENCS</u>	<u>Korea KECI/KECL</u>	<u>China IECSC</u>	<u>NewZealand IOC</u>
Acetone	67-64-1	200-662-2	Present	Present	(2)-542	KE-29367	Present	HSR001070
p-Chlorobenzotrifluoride	98-56-6	202-681-1	Present	Present	(3)-53	KE-05928	Present	HSR005269 (dilution)
Chromium and compounds	7440-47-3	231-157-5	Present	Present	Not listed	KE-05970	Present	HSR002943
Manganese (and compounds)	7439-96-5	231-105-1	Present	Present	Not listed	KE-22999	Present	HSR003013
n-Butyl alcohol	71-36-3	200-751-6	Present	Present	(2)-3049	KE-03867	Present	HSR001096
Xylene	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983
n-Butyl-acetate	123-86-4	204-658-1	Present	Present	(2)-735; (2)-731	KE-04179	Present	HSR001091
Toluene	108-88-3	203-625-9	Present	Present	(3)-2	KE-33936	Present	HSR001227
Petroleum Distillates	8052-41-3	232-489-3	Present	Present	(9)-1702; (9)-1702	KE-32199	Present	HSR001498

SECTION 16. OTHER INFORMATION

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- AICS: Australian Inventory of Chemical Substances
- CA: California
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- CSA: Canadian Standards Association
- DOT: Department of Transportation
- EC50: Effective Concentration 50%.
- EINECS: European Inventory of Existing Commercial chemical Substances
- ENCS: Existing and New Chemical Substances
- EPA: Environmental Protection Agency
- HMIS: Hazardous Materials Identification System
- HSDB: Hazardous Substances Data Bank
- IARC: International Agency for Research on Cancer
- IECSC: Inventory of Existing Chemical Substances
- IMDG: International Maritime Dangerous Goods
- Inh: Inhalation
- KECI: Korean Existing Chemicals Inventory
- KECL: Korean Existing Chemicals List
- LC: Lethal Concentration
- LD: Lethal Dose
- N/Ap: Not Applicable
- N/Av: Not Available
- NFPA: National Fire Protection Association
- NJ: New Jersey
- NIOSH: National Institute of Occupational Safety and Health
- NOEC: No observable effect concentration
- NTP: National Toxicology Program
- OECD: Organisation for Economic Co-operation and Development
- OSHA: Occupational Safety and Health Administration
- PA: Pennsylvania
- PEL: Permissible exposure limit
- PICCS: Philippine Inventory of Chemicals and Chemical Substances



Dampney Company, Inc.
 85 Paris Street
 Everett, Massachusetts, U.S.A. 02149
 Email: sales@dampney.com
 Telephone: (617) 389 2805

Thurmalox 242C-02

SDS Preparation Date (mm/dd/yyyy): 12/29/2015

Page 14 of 14

SAFETY DATA SHEET

RCRA: Resource Conservation and Recovery Act
 RTECS: Registry of Toxic Effects of Chemical Substances
 SARA: Superfund Amendments and Reauthorization Act
 STEL: Short Term Exposure Limit
 TDG: Canadian Transportation of Dangerous Goods Act & Regulations
 TLV: Threshold Limit Values
 TPQ: Threshold Planning Quantity
 TSCA: Toxic Substance Control Act
 TWA: Time Weighted Average
 WHMIS: Workplace Hazardous Materials Identification System

References

: Canadian Centre for Occupational Health and Safety, CCHInfoWeb databases, 2015 (Chempendium, RTECs, HSDB, INCHEM).
 OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015
 European Chemicals Agency, Classification Legislation, 2015
 Material Safety Data Sheet from manufacturer.

Preparation Date (mm/dd/yyyy)

: 12/29/2015

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

<p>Prepared for: Dampney Company, Inc. 85 Paris Street Everett MA 02149 U.S.A Telephone: (617) 389-2805 Please direct all inquiries to Dampney Company.</p>	
<p>Prepared by: ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.); (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from Dampney Company, Inc and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Dampney Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and Dampney Company, Inc.

END OF DOCUMENT