

Email: sales@dampney.com Telephone: (617) 389 2805

Page: 1 of 9

Thurmalox 280C

SDS Preparation Date (mm/dd/yyyy): 10/16/2024

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label: Thurmalox Aluminum

Product Code(s): 280C

Recommended use of the chemical and restrictions on use: Heat Resistant Aluminum Coating

Use pattern: Professional use only Recommended restrictions: None known.

Chemical family: Mixture

Name, address, and telephone number of the manufacturer:

Dampney Company, Inc.

85 Paris Street

Everett, Massachusetts, U.S.A. 02149

Email: sales@dampney.com

Supplier's Telephone: (617) 389-2805

24 Hr. Emergency Tel: Chemtrec 1-800-424-9300 (Within North America).

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Silver liquid. Solvent odor.

Most important hazards: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification:

Flammable Liquids - Category 2 Skin Irritation - Category 2

Serious eye damage/eye irritation - Category 2A Reproductive Toxicity - Category 2

Carcinogen - Category 2

Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects

Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory)

Specific Target Organ Toxicity, Repeated Exposure - Category 2 (CNS)

Label elements

Hazard pictogram(s)



Signal Word DANGER!

Hazard statement(s)

Highly flammable liquid and vapour. Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging the unborn child. Suspected of causing cancer.

May cause drowsiness or dizziness. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statement(s)

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, open flames, and hot surfaces. - No smoking.

Keep container tightly closed.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe mist or vapor.

Wash hands thoroughly after handling.



Email: sales@dampney.com

Telephone: (617) 389 2805

Page: 2 of 9

Thurmalox 280C

SDS Preparation Date (mm/dd/yyyy): 10/16/2024

SAFETY DATA SHEET

Use only outdoors or in a well-ventilated area.

Wear protective gloves/clothing and eye/face protection.

Response:

If exposed or concerned: Get medical attention/advice.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before

If skin irritation occurs, get medical advice/attention.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use water fog, dry chemical, CO2, or 'alcohol' foam for extinction.

Storage:

Store locked up.

Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal:

Dispose of contents/container in accordance with local regulation.

Other hazards

No OSHA defined hazard classes.

Other hazards which do not result in classification:

Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	Common name and synonyms	CAS#	Concentration
p-Chlorobenzotrifluoride	PCBFT	98-56-6	35.44
Aluminum powder	Aluminum flake	7429-90-5	19.31
Petroleum Distillates	Mineral spirits White spirit	8052-41-3	9.08
Aromatic hydrocarbon	Aromatic naphtha	64742-95-6	4.55
Toluene	Methylbenzene Phenylmethane	108-88-3	3.52

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact; Immediately flush with plenty of water, while removing contaminated clothing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Eye contact: For eye contact, flush with running water for at least 15 minutes. If eye irritation persists: get medical advice/attention.

Most important symptoms and effects, both acute and delayed: Causes skin irritation. Redness, swelling, itching and dryness. May cause respiratory irritation. May cause coughing and breathing difficulties. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause headache, nausea, dizziness, and other symptoms of central nervous system depression. Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis. Suspected of damaging fertility or the unborn child. May cause damage to the central nervous system through prolonged or repeated exposure if inhaled. Suspected of causing cancer.

Indication of any immediate medical attention and special treatment needed: Treat symptomatically. This product is a CNS depressant.



Email: sales@dampney.com Telephone: (617) 389 2805

Page: 3 of 9

Thurmalox 280C

SDS Preparation Date (mm/dd/yyyy): 10/16/2024

SAFETY DATA SHEET

Extinguishing media

Suitable extinguishing media: Carbon dioxide (CO2); Dry chemical; Alcohol resistant foam; Water fog.

Unsuitable extinguishing media: Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability: Highly flammable liquid and vapour. Vapours may ignite explosively. Vapours are heavier than air and may spread along floors. Static discharge, impact, friction, and heat may ignite exposed chemical material.

Flammability classification (OSHA 29 CFR 1910.106): Flammable Liquids - Category 2

Hazardous combustion products: Carbon dioxide, carbon monoxide and other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures: Do not breathe fumes or vapours. Move containers from fire area if safe to do so. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Do not allow run-off from firefighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions: Do not allow material to contaminate ground water system. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

Methods and material for containment and cleaning up: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools and equipment in the clean-up process. Avoid breathing mist or vapours. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contact the proper local authorities. Refer to Section 13 for disposal of contaminated material.

Special spill response procedures: In case of a transportation accident, contact CHEMTREC at 1-800-424-9300. EPA/CERCLA Reportable quantity (RQ): Toluene (1000 lbs / 454 kg)

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/clothing and eye/face protection. Use only in well-ventilated areas. Do not breathe mist or vapor. Avoid contact with skin, eyes, and clothing. Keep container tightly closed. Do not eat, drink, or smoke when using this product. Wash thoroughly after handling. Keep away from flames and hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharges. Ground all equipment during handling.

Conditions for safe storage: Keep container tightly closed. Store in cool/well-ventilated place. Store locked up. Keep cool. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Empty containers may contain hazardous residues.

Incompatible materials: Strong oxidizers, acids, and bases.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

Chemical Name	ACGIH TL\	/	OSHA PEL			
	TWA	STEL	PEL	STEL		
p-Chlorobenzotrifluoride	N/Av	N/Av	N/Av	N/Av		
Aluminum powder	1 mg/m³ (respirable)	N/Av	15 mg/m³ (total dust)/5 mg/m³ (respirable)	N/Av		
Petroleum Distillates	100 ppm	N/Av	500 ppm (2900 mg/m³)	N/Av		
Aromatic hydrocarbon	N/Av	N/Av	N/Av	N/Av		
Toluene	20 ppm	N/Av	200 ppm	300 ppm (Ceiling)		



Telephone: (617) 389 2805

Page: 4 of 9

Thurmalox 280C

SDS Preparation Date (mm/dd/yyyy): 10/16/2024

SAFETY DATA SHEET

Exposure controls

Ventilation and engineering measures: Use only in well-ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection: If airbourne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection specialists.

Skin protection: Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron, and boots to prevent contact. Advice should be sought from glove suppliers.

Eye / face protection: Wear chemical goggles.

Other protective equipment: Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations: Do not breathe mist or vapor. Avoid contact with skin, eyes, and clothing. Do not eat, drink, or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Silver liquid.
Odour : Solvent odor.

pH : No information available.

Melting/Freezing point : Not available.
Initial boiling point and boiling range : 228.0 – 396.0°F
Flash point : 81.0 - 118.4°F

Flashpoint (Method) : Closed cup

Evaporation rate (BuAe = 1) : 0.272 slower than n-butyl acetate.

Flammability (solid, gas) : Not applicable.

Lower flammable limit (% by vol.) : 1.0%
Upper flammable limit (% by vol.) : 7.0%

Explosive properties : Not explosive Vapour pressure : Not available. Vapour density : > 1
Relative density / Specific gravity : 1.47618
Weight per gallon : 12.36

Solubility in water : N/Ap

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

2. Not available.

Auto-ignition temperature
2. Viscosity
3. 300 cSt at 40°C

Volatiles (% by weight)
3. Kot available.
3. Not available.

Volatiles (% by weight) : 62.0%
Volatiles (% by volume) : 48.0%
Volatile organic Compounds (VOC's) : 3.48 lbs/gal

Other physical/chemical comments : None known or reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not normally reactive.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Hazardous polymerization does not occur.

Conditions to avoid: Open flames, sparks, high heat, direct sunlight, and close proximity to incompatible substances. Do not use in areas without adequate ventilation.

Incompatible materials: Strong oxidizers, acids, and bases.

Hazardous decomposition products: See Section 5 (Fire Fighting Measures).



Telephone: (617) 389 2805

Page: 5 of 9

Thurmalox 280C

SDS Preparation Date (mm/dd/yyyy): 10/16/2024

SAFETY DATA SHEET

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation: YES Routes of entry skin & eye: YES Routes of entry Ingestion: YES

Routes of exposure skin absorption: YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation: May cause respiratory tract irritation. Symptoms may include sore throat, running nose and shortness of breath. May cause headache, nausea, dizziness, and other symptoms of central nervous system depression.

Sign and symptoms ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin: Causes skin irritation. Symptoms may include redness, edema, drying defatting, and cracking of the skin.

Sign and symptoms eyes: Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

Potential Chronic Health Effects: Prolonged exposure can cause central nervous system effects.

Mutagenicity: Not expected to be mutagenic in humans.

Carcinogenicity: Not expected to be carcinogenic in humans.

Reproductive effects & Teratogenicity: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Reproductive Toxicity - Category 2 Suspected of damaging the unborn child.

Contains Toluene. Toluene may cause fetotoxic effects at doses which are not maternally toxic, based on animal data.

Sensitization to material: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects: This material is classified as hazardous under OSHA regulations (29CFR 1910.1200)

(Hazcom 2012). Classification:

Specific target organ toxicity, single exposure - Category 3.

May cause drowsiness or dizziness.

May cause respiratory irritation.

Specific target organ toxicity (STOT), repeated exposure - Category 2 May cause damage to the central nervous system through prolonged or repeated exposure if inhaled.

Medical conditions aggravated by overexposure: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials: No information available.

Toxicological data: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data. See below for toxicological data on the substance.

Chamical mana	LC50(4hr)	LD50				
Chemical name	inh, rat ´	(Oral, rat)	(Rabbit, dermal)			
p-Chlorobenzotrifluoride	33 mg/L 4 h	13 g/kg	N/Av			
Aluminum powder	> 2.3 mg/L (dust) (No mortality)	> 2000 mg/kg (No mortality)	N/Av			
Petroleum Distillates	> 5.5 mg/L (vapour)	> 5000 mg/kg	> 3000 mg/kg			
Aromatic hydrocarbon	atic hydrocarbon > 17.7 mg/L (vapour)		> 3160 mg/kg			
Toluene	luene 7585 ppm (28.1 mg/L) (vapour)		12 125 mg/kg			

Other important toxicological hazards: None reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: Contains material that may be harmful in the environment. Do not allow material to contaminate ground water system. See data for individual ingredient ecotoxicity data.

Ecotoxicity data:



Telephone: (617) 389 2805

Page: 6 of 9

Thurmalox 280C

SDS Preparation Date (mm/dd/yyyy): 10/16/2024

SAFETY DATA SHEET

Ingredients	CACNO	Toxici	ty to Fish	
	CAS No	LC50 / 96h	NOEC / 21 day	M Factor
p-Chlorobenzotrifluoride	98-56-6	3 mg/L (Zebra fish)	N/Av	None.
Aluminum powder	7429-90-5	N/Av	N/Av	None.
Petroleum Distillates	8052-41-3	2.1 - 4.2 mg/L (Bluegill sunfish)	N/Av	None.
Aromatic hydrocarbon	64742-95-6	9.22 mg/L (Rainbow trout)	N/Av	None.
Toluene	108-88-3	5.4 mg/L (pink salmon)	1.4 - 4.0 mg/L	None.

la ana dia ata	CACNE	Toxicity to Daphnia					
Ingredients	CAS No	EC50 / 48h	NOEC / 21 day	M Factor			
p-Chlorobenzotrifluoride	98-56-6	2mg/L (Daphnia magna)	N/Av	None.			
Aluminum powder	7429-90-5	N/Av	N/Av	None.			
Petroleum Distillates	8052-41-3	0.42 - 2.3 mg/L (Daphnia magna) (Closed systems - low end; Open systems - high end)	0.1 - 0.37 mg/L	None.			
Aromatic hydrocarbon	64742-95-6	6.16 mg/L (Daphnia magna)	N/Av	None.			
Toluene	108-88-3	3.78 mg/L Ceriodaphnia (water flea)	0.53 - 1 mg/L	None.			

In our diame	CACNA	Toxicity to Algae						
Ingredients	CAS No	EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor				
p-Chlorobenzotrifluoride	98-56-6	>0.41 mg/L (Green algae)	>0.41 mg/L (Green algae)	None.				
Aluminum powder	7429-90-5	N/Av	N/Av	None.				
Petroleum Distillates	8052-41-3	0.58 - 1.2 mg/L/72hr (Green algae) (Closed systems - low end; Open systems - high end)	0.16 mg/L/72hr	None.				
Aromatic hydrocarbon	64742-95-6	N/Av	N/Av	N/Av				
Toluene	108-88-3	N/Av	10 mg/L/72hr (Green algae)	None.				

Persistence and degradability: No data is available on the product itself.

Bioaccumulation potential: No data is available on the product itself.

Components	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)		
p-Chlorobenzotrifluoride	3.7 at 25 °C	121-202		
Aluminum powder	N/Ap	N/Ap		
Petroleum Distillates	3.16 - 7.06	N/Av		
Aromatic hydrocarbon	2.1 - 6 (calculated)	10-2500		
Toluene	2.65	90		

Mobility in soil: No data is available on the product itself. Other Adverse Environmental effects: None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

Methods of Disposal: Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state, and federal environmental agencies.



Email: sales@dampney.com Telephone: (617) 389 2805

Page: 7 of 9

Thurmalox 280C SDS Preparation Date (mm/dd/yyyy): 10/16/2024

SAFETY DATA SHEET

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1263	Paint	3	III	
Additional information		ted as a limited quantity the maximum net capacity specified CFR for inner packagings may be increased to 5L (1.3 gallown 149.	` '	` '	3
TDG	UN1263	PAINT	3	III	
Additional information		d as Limited Quantity when transported in containers no larg xceeding 30 kg gross mass.	ger than 5.0 Liti	res; in	3
IMDG	UN1263	Paint	3	III	
Additional information	, , , , , ,	d as Limited Quantity when transported in containers no larg xceeding 30 kg gross mass.	ger than 5.0 Liti	res; in	3
ICAO/IATA	UN1263	Paint	3	III	
Additional information	Refer to the app	propriate Packing Instruction, prior to shipping this material.			3

Special precautions for user: Appropriate advice on safety must accompany the package.

Environmental hazards: See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: This information is not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

Ingredients	CAS#	TSCA	CERCLA Reportable	SARA TITLE III: Sec. 302, Extremely Hazardous		Sec. 313, 40 CFR oxic Chemical
Ingredients	OAO #	Inventory	Quantity (RQ) (40 CFR 117.302):	Substance, 40 CFR 355:	Toxic Chemical	de minimus Concentration
p-Chlorobenzotrifluoride	98-56-6	Yes	N/Ap	N/Av	No	N/Ap
Aluminum powder	7429-90-5	Yes	None.	None.	Yes	1%
Petroleum Distillates	8052-41-3	Yes	None.	None.	No	N/Ap
Aromatic hydrocarbon	64742-95-6	Yes	None.	None.	No	N/Ap
Toluene	108-88-3	Yes	1000 lb/ 454 kg	None.	Yes	1%

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Immediate (Acute) health hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws: The following chemicals are specifically listed by individual States:

Ingredients	CAS#	California	Proposition 65		State	e "Right t	o Know"	Lists	
ingredients	CAS#	Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI



Everett, Massachusetts, U.S.A 02149 Email: sales@dampney.com

Telephone: (617) 389 2805

Page: 8 of 9

Thurmalox 280C

SDS Preparation Date (mm/dd/yyyy): 10/16/2024

SAFETY DATA SHEET

p-Chlorobenzotrifluoride	98-56-6	No	N/Ap	No	No	No	No	No	No
Aluminum powder	7429-90-5	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Petroleum Distillates	8052-41-3	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Aromatic hydrocarbon	64742-95-6	No	N/Ap	No	No	No	No	No	No
Toluene	108-88-3	No	Developmental	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information: Canadian Environmental Protection Act (CEPA): All ingredients are present on the DSL. WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

International Information: Components listed below are present on the following International Inventory list:

Ingredients	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
p-Chlorobenzotrifluoride	98-56-6	202-681-1	Present	Present	(3)-53	KE-05928	Present	HSR005269 (dilution)
Aluminum powder	7429-90-5	231-072-3	Present	Present	Not listed	KE-00881	Present	HSR001263 (coated, PGII); HSNO Approval: HSR001471, HSR001473 (coated, PGIII); HSNO Approval: HSR001474 (pyrophoric); HSNO Approval: H SR001472 (uncoated, PGII)
Petroleum Distillates	8052-41-3	232-489-3	Present	Present	(9)-1702; (9)- 1702	KE-32199	Present	HSR001498
Aromatic hydrocarbon	64742-95-6	265-199-0	Present	Present	(9)-1698	KE-31662	Present	No information
Toluene	108-88-3	203-625-9	Present	Present	(3)-2	KE-33936	Present	HSR001227

SECTION 16. OTHER INFORMATION

Legend:

ACGIH: American Conference of Governmental Industrial Hygienists

AICS: Australian Inventory of Chemical Substances

ATE: Acute Toxicity Estimate

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980

CFR: Code of Federal Regulations
CSA: Canadian Standards Association

CSA: Canadian Standards Association
DOT: Department of Transportation ECHA: European Chemicals Agency

ECOTOX: U.S. EPA Ecotoxicology Database

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS: Existing and New Chemical Substances EPA: Environmental Protection Agency HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

IBC: Intermediate Bulk Container

IECSC: Inventory of Existing Chemical Substances IMDG: International Maritime Dangerous Goods

IOC: Inventory of Chemicals

IUCLID: International Uniform Chemical Information Database

KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List

LC: Lethal Concentration

LD: Lethal Dose



Telephone: (617) 389 2805

Page: 9 of 9

Thurmalox 280C

SDS Preparation Date (mm/dd/yyyy): 10/16/2024

SAFETY DATA SHEET

MA: Massachusetts MN: Minnesota N/Ap: Not Applicable N/Av: Not Available

NIOSH: National Institute of Occupational Safety and Health

NJ: New Jersey

NOEC: No observable effect concentration NTP: National Toxicology Program

OECD: Organization for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PA: Pennsylvania

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

RCRA: Resource Conservation and Recovery Act

RI: Rhode Island

RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act SDS: Safety Data Sheet / Material Safety Data Sheet

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TSCA: Toxic Substance Control Act TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

References:

ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2015. International Agency for Research on Cancer Monographs, searched 2015.

Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2015 (Chempendium, HSDB and RTECs).

Material Safety Data Sheets from manufacturer. US EPA Title III List of Lists - 2015 version. California Proposition 65 List -2015 version

Preparation Date (mm/dd/yyyy): 01/28/2016

Other special considerations for handling: Provide adequate information, instruction, and training for operators.

Prepared by:

Dampney Company, Inc. 85 Paris Street Everett MA 02149 U.S.A Telephone: (617) 389-2805



DISCLAIMER

This Safety Data Sheet was prepared by Dampney Company, Inc. and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Dampney Company, Inc. expressly disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this Safety Data Sheet does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Dampney Company, Inc.

END OF DOCUMENT