



Thurmalox 8704K  
SDS Preparation Date (mm/dd/yyyy): 01/12/2022

Page 1 of 8

## SAFETY DATA SHEET

### SECTION 1. IDENTIFICATION

**Product identifier used on the label: Thurmalox 8704K**  
**Product Code(s):** 8704K Aluminum

**Recommended use of the chemical and restrictions on use:** Heat resistant coating  
Use pattern: Professional use only  
Recommended restrictions: None known.

**Chemical family** : Mixture

**Name, address, and telephone number of the manufacturer:**  
**Dampney Company, Inc.**  
85 Paris Street  
Everett, Massachusetts, U.S.A. 02149

Email: sales@dampney.com

Supplier's Telephone #: (617) 389-2805

**24 Hr. Emergency Tel #:** Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887(Outside U.S.).

### SECTION 2. HAZARDS IDENTIFICATION

**Classification of the chemical**  
Silver liquid. Solvent odor.

Most important hazards: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification:

Acute toxicity (Inhalation) – Category 4  
Acute toxicity (Oral) – Category 4  
Eye irritation – Category 2  
Flammable Liquid – Category 2  
Specific Target Organ Toxicity - Single Exposure – Category 3 (Narcotic effects)

#### Label elements

*Hazard pictogram(s)*



*Signal Word*  
DANGER!

*Hazard statement(s)*  
H225 Highly flammable liquid and vapour.  
H302 Harmful if swallowed.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.

*Prevention*  
P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical, ventilating, lighting, mixing, application equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust, fume, gas, mist, vapours, or spray.  
P264 Wash hands thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection, and face protection.

*Response*



Thurmalox 8704K  
SDS Preparation Date (mm/dd/yyyy): 01/12/2022

Page 2 of 8

## SAFETY DATA SHEET

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or hospital emergency room.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 Call a POISON CENTER, doctor, or hospital emergency room if you feel unwell.  
P330 Rinse mouth.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P370 + P378 In case of fire: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam to extinguish.

### Storage:

P403 + P233 + P235 (S) Store in a cool, well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents and empty container in accordance with local, state and federal regulations.

### Other hazards

No OSHA defined hazard classes.

Other hazards which do not result in classification:

Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	Common name and synonyms	CAS #	Concentration
Acetone	Acetone	67-64-1	52.65
Aluminum powder	Alumina	7429-90-5	15.41
Methyl Amyl Ketone	Methyl Amyl Ketone	110-43-0	8.83
Petroleum Distillates	Mineral spirits White spirit	8052-41-3	7.25

## SECTION 4. FIRST-AID MEASURES

### Description of first aid measures

**Ingestion:** Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

**Inhalation:** If inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Call a POISON CENTRE or doctor/physician if you feel unwell.

**Skin contact:** Immediately flush with plenty of water, while removing contaminated clothing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

**Eye contact:** For eye contact, flush with running water for at least 15 minutes. If eye irritation persists: get medical advice/attention.

### Most important symptoms and effects, both acute and delayed

- : Causes skin irritation. Redness, swelling, itching and dryness. May cause respiratory irritation. May cause coughing and breathing difficulties. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause headache, nausea, dizziness and other symptoms of central nervous system depression. Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis. Suspected of damaging fertility or the unborn child. May cause damage to the central nervous system through prolonged or repeated exposure if inhaled. Suspected of causing cancer.

### Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically. This product is a CNS depressant.

## SECTION 5. FIRE-FIGHTING MEASURES

### Extinguishing media

**Suitable extinguishing media:** Carbon dioxide (CO<sub>2</sub>); Dry chemical; Alcohol resistant foam; Water fog. .

**Unsuitable extinguishing media:** Do not use a solid water stream as it may scatter and spread fire.

**Special hazards arising from the substance or mixture / Conditions of flammability:** Highly flammable liquid and vapour. Vapours may ignite explosively. Vapours are heavier than air and may spread along floors. Static discharge, impact, friction, and heat may ignite exposed chemical material.

**Flammability classification (OSHA 29 CFR 1910.106):** Flammable Liquids - Category 2

**Hazardous combustion products:**



**SAFETY DATA SHEET**

Carbon dioxide, carbon monoxide and other unidentified organic compounds.

**Special protective equipment and precautions for firefighters**

*Protective equipment for fire-fighters:* Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

*Special fire-fighting procedures:* Do not breathe fumes or vapours. Move containers from fire area if safe to do so. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures:** All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

**Environmental precautions:** Do not allow material to contaminate ground water system. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

**Methods and material for containment and cleaning up:** Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools and equipment in the clean-up process. Avoid breathing mist or vapours. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contact the proper local authorities. Refer to Section 13 for disposal of contaminated material.

**Special spill response procedures:** In case of a transportation accident, contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. EPA/CERCLA.

Reportable quantity (RQ): None

**SECTION 7. HANDLING AND STORAGE**

**Precautions for safe handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/clothing and eye/face protection. Use only in well-ventilated areas. Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Keep container tightly closed. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Keep away from flames and hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharges. Ground all equipment during handling.

**Conditions for safe storage:** Keep container tightly closed. Store in cool, well-ventilated place. Store locked up. Keep cool. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Empty containers may contain hazardous residues.

**Incompatible materials:** Strong oxidizers, acids and bases.

**SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Limits:**

Chemical Name	ACGIH TLV		OSHA PEL	
	TWA	STEL	PEL	STEL
Acetone	N/A	750 ppm	1000 ppm 2400 mg/m <sup>3</sup>	N/A
Aluminum powder	1 mg/m <sup>3</sup> (respirable)	N/Av	15 mg/m <sup>3</sup> (total dust); 5 mg/m <sup>3</sup> (respirable)	N/Av
Methyl Amyl Ketone	50 ppm	N/Av	100 ppm	N/Av
Petroleum Distillates	100 ppm	N/Av	500 ppm (2900 mg/m <sup>3</sup> )	N/Av

**Exposure controls**

**Ventilation and engineering measures:** Use only in well-ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

**Respiratory protection:** If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection specialists.

**Skin protection:** Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. Advice should be sought from glove suppliers.

**Eye / face protection:** Wear chemical goggles.

**Other protective equipment:** Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

**General hygiene considerations:** Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**



Thurmalox 8704K  
 SDS Preparation Date (mm/dd/yyyy): 01/12/2022

**SAFETY DATA SHEET**

**Appearance:** Silver liquid.  
**Odour:** Solvent odor.  
**pH:** No information available.  
**Melting/Freezing point:** Not available.  
**Initial boiling point and boiling range:** 133.0 - 396.0°F  
**Flash point:** 1.4 - 102°F  
**Flashpoint(Method):** Closed cup  
**Evaporation rate (BuAe = 1):** 7.546 times faster than n-Butyl Acetate  
**Flammability (solid, gas):** Not applicable.  
**Lower flammable limit (% by vol.) :** 1.0%  
**Upper flammable limit (% by vol.) :** 7.0%  
**Oxidizing properties:** None known.  
**Explosive properties** Not explosive  
**Vapour pressure:** Not available  
**Vapour density:** > 1  
**Relative density / Specific gravity:** 0.94314  
**Auto-ignition temperature:** Not available.  
**Decomposition temperature:** No information available.  
**Volatiles (% by weight):** 69.00%  
**Volatiles (% by volume):** 82.00%  
**Weight per gallon:** 7.9 lbs  
**Volatile organic Compounds (VOC's):** 3.48 lbs/gal

**SECTION 10. STABILITY AND REACTIVITY**

**Reactivity:** Not normally reactive.  
**Chemical stability:** Stable under normal conditions.  
**Possibility of hazardous reactions:** Hazardous polymerization does not occur.  
**Conditions to avoid:** Open flames, sparks, high heat, direct sunlight, and close proximity to incompatible substances. Do not use in areas without adequate ventilation.  
**Incompatible materials:** Strong oxidizers, acids and bases.  
**Hazardous decomposition products:** See Section 5 (Fire Fighting Measures).

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure:**

**Routes of entry inhalation:** YES  
**Routes of entry skin & eye:** YES  
**Routes of entry Ingestion:** YES  
**Routes of exposure skin absorption:** YES  
**Potential Health Effects:**

**Signs and symptoms of short-term (acute) exposure**

*Sign and symptoms Inhalation:* May cause respiratory tract irritation. Symptoms may include sore throat, running nose and shortness of breath. May cause headache, nausea, dizziness and other symptoms of central nervous system depression.  
*Sign and symptoms ingestion:* Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.  
*Sign and symptoms skin:* Causes skin irritation. Symptoms may include redness, edema, drying defatting and cracking of the skin.  
*Sign and symptoms eyes:* Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

**Potential Chronic Health Effects:**

Prolonged exposure can cause central nervous system effects.  
**Mutagenicity:** Not expected to be mutagenic in humans.  
**Carcinogenicity:** Not expected to be carcinogenic in humans.  
**Reproductive effects & Teratogenicity:** None.  
**Sensitization to material:** Not expected to be a skin or respiratory sensitizer.  
**Specific target organ effects:** This material is classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012). Classification:  
 Specific target organ toxicity, single exposure - Category 3. May cause drowsiness or dizziness.  
 May cause respiratory irritation.

Specific target organ toxicity (STOT), repeated exposure - Category 2 May cause damage to the central nervous system through prolonged or repeated exposure if inhaled.

**Medical conditions aggravated by overexposure:** Pre-existing skin, eye, respiratory and central nervous system disorders.

**Synergistic materials:** No information available.

**Toxicological data:** There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data. See below for toxicological data on the substance.

Chemical name	LC50(4hr) inh, rat	LD50	
		(Oral, rat)	(Rabbit, dermal)



**SAFETY DATA SHEET**

Acetone	> 20.0 mg/L	> 2,000 mg/kg	>2,000 mg/kg
Aluminum powder	> 2.3 mg/L (dust) (No mortality)	> 2,000 mg/kg (No mortality)	N/Av
Methyl Amyl Ketone	16.7 mg/L	1,600 mg/kg	>2,001 mg/kg
Petroleum Distillates	> 5.5 mg/L (vapour)	> 5,000 mg/kg	> 3,000 mg/kg

**Other important toxicological hazards:** None reported by the manufacturer.

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity:** Contains material that may be harmful in the environment. Do not allow material to contaminate ground water system. See data for individual ingredient ecotoxicity data.

**Ecotoxicity data:**

Ingredients	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Acetone	67-64-1	100 mg/l (rainbow trout)	N/Av	None.
Aluminum powder	7429-90-5	N/Av	N/Av	None.
Methyl Amyl Ketone	110-43-0	N/Av	N/Av	None.
Petroleum Distillates	8052-41-3	2.1 - 4.2 mg/L (Bluegill sunfish)	N/Av	None.

Ingredients	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Acetone	67-64-1	100 mg/l (water flea)	N/Av	None.
Aluminum powder	7429-90-5	N/Av	N/Av	None.
Methyl Amyl Ketone	110-43-0	N/Av	N/Av	None.
Petroleum Distillates	8052-41-3	0.42 - 2.3 mg/L (Daphnia magna) (Closed systems - low end; Open systems - high end)	0.1 - 0.37 mg/L	None.

Ingredients	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Acetone	67-64-1	100 mg/l (green algae)	N/Av	None.
Aluminum powder	7429-90-5	N/Av	N/Av	None.
Methyl Amyl Ketone	110-43-0	N/Av	N/Av	None.
Petroleum Distillates	8052-41-3	0.58 - 1.2 mg/L/72hr (Green algae) (Closed systems - low end; Open systems - high end)	0.16 mg/L/72hr	None.

**Persistence and degradability:** No data is available on the product itself.

**Bioaccumulation potential:** No data is available on the product itself.

Components	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
Acetone	-0.24	N/Av
Aluminum powder	N/Av	N/Av
Methyl Amyl Ketone	N/Av	N/Av
Petroleum Distillates	3.16 - 7.06	N/Av

**Mobility in soil:** No data is available on the product itself.

**Other Adverse Environmental effects:** None known.



Thurmalox 8704K  
 SDS Preparation Date (mm/dd/yyyy): 01/12/2022

**SAFETY DATA SHEET**

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Handling for Disposal:** Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

**Methods of Disposal:** Dispose in accordance with all applicable federal, state, provincial and local regulations.

**RCRA:** If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

**SECTION 14. TRANSPORTATION INFORMATION**

Regulatory Information	UN Number	UN proper shipping name	Hazard class(es)	Packing Group	Label
49CFR/DOT Additional information	UN1263	Paint	3	II	Flammable
	When transported as a limited quantity the maximum net capacity specified in 173.150(b)(2) of the subchapter 49CFR for inner packagings may be increased to 5L (1.3 gallons) 172.102(C)(1)(149) special provision 149.				
TDG Additional information	UN1263	PAINT	3	II	Flammable
	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass.				
IMDG Additional information	UN1263	Paint	3	II	Flammable
	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass.				
ICAO/IATA Additional information	UN1263	Paint	3	II	Flammable
	Refer to the appropriate Packing Instruction, prior to shipping this material.				

**Special precautions for user:** Appropriate advice on safety must accompany the package.

**Environmental hazards:** See ECOLOGICAL INFORMATION, Section 12.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** This information is not available.

**SECTION 15 - REGULATORY INFORMATION**

**US Federal Information:**

Components listed below are present on the following U.S. Federal chemical lists:

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Acetone	67-64-1	Yes	None.	None.	No	N/Ap
Aluminum powder	7429-90-5	Yes	None.	None.	Yes	1%
Methyl Amyl Ketone	110-43-0	Yes	None	None.	No	N/Ap
Petroleum Distillates	8052-41-3	Yes	None.	None.	No	N/Ap

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Immediate (Acute) health hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

**US State Right to Know Laws:**

The following chemicals are specifically listed by individual States:

Ingredients	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI



**SAFETY DATA SHEET**

Acetone	67-64-1	No	N/Ap	No	Yes	No	Yes	Yes	Yes
Aluminum powder	7429-90-5	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Methyl Amyl Ketone	110-43-0	No	N/Ap	No	Yes	No	Yes	Yes	No
Petroleum Distillates	8052-41-3	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes

**Canadian Information:**

Canadian Environmental Protection Act (CEPA): All ingredients are present on the DSL. WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

**International Information:**

Components listed below are present on the following International Inventory list:

Ingredients	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Acetone	67-64-1	200-662-2	Present	Present	2-542	KE-29367	Present	Present
Aluminum powder	7429-90-5	231-072-3	Present	Present	Not listed	KE-00881	Present	Present
Methyl Amyl Ketone	110-43-0	203-767-1	Present	Present	Present	Present	Present	Present
Petroleum Distillates	8052-41-3	232-489-3	Present	Present	(9)-1702; (9)-1702	KE-32199	Present	HSR001498

**SECTION 16. OTHER INFORMATION**

**Legend:**

- ACGIH: American Conference of Governmental Industrial Hygienists
- AICS: Australian Inventory of Chemical Substances
- ATE: Acute Toxicity Estimate
- CA: California
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- CSA: Canadian Standards Association
- DOT: Department of Transportation
- ECHA: European Chemicals Agency
- ECOTOX: U.S. EPA Ecotoxicology Database
- EINECS: European Inventory of Existing Commercial chemical Substances
- ENCS: Existing and New Chemical Substances
- EPA: Environmental Protection Agency
- HSDB: Hazardous Substances Data Bank
- IARC: International Agency for Research on Cancer
- IBC: Intermediate Bulk Container
- IECSC: Inventory of Existing Chemical Substances
- IMDG: International Maritime Dangerous Goods
- IOC: Inventory of Chemicals
- IUCLID: International Uniform Chemical Information Database
- KECI: Korean Existing Chemicals Inventory
- KECL: Korean Existing Chemicals List
- LC: Lethal Concentration
- LD: Lethal Dose
- MA: Massachusetts
- MN: Minnesota
- N/Ap: Not Applicable
- N/Av: Not Available
- NIOSH: National Institute of Occupational Safety and Health
- NJ: New Jersey
- NOEC: No observable effect concentration
- NTP: National Toxicology Program
- OECD: Organization for Economic Co-operation and Development
- OSHA: Occupational Safety and Health Administration
- PA: Pennsylvania
- PEL: Permissible exposure limit
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- RCRA: Resource Conservation and Recovery Act
- RI: Rhode Island
- RTECS: Registry of Toxic Effects of Chemical Substances
- SARA: Superfund Amendments and Reauthorization Act
- SDS: Safety Data Sheet / Material Safety Data Sheet



Thurmalox 8704K  
SDS Preparation Date (mm/dd/yyyy): 01/12/2022

### SAFETY DATA SHEET


STEL: Short Term Exposure Limit  
TDG: Canadian Transportation of Dangerous Goods Act & Regulations  
TLV: Threshold Limit Values  
TSCA: Toxic Substance Control Act  
TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Identification System

**References:**

1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2015.
2. International Agency for Research on Cancer Monographs, searched 2015.
3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2015 (Chempendium, HSDB and RTECs).
4. Material Safety Data Sheets from manufacturer.
5. US EPA Title III List of Lists - 2015 version.
6. California Proposition 65 List -2015 version

**Preparation Date (mm/dd/yyyy):** 01/12/2022

**Other special considerations for handling:** Provide adequate information, instruction and training for operators.

<p><b>Prepared by:</b> Dampney Company, Inc. 85 Paris Street Everett MA 02149 U.S.A Telephone: (617) 389-2805 Please direct all inquiries to Dampney Company.</p>	
---	---

**DISCLAIMER**

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Dampney Company, Inc. and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Dampney Company, Inc. expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this Safety Data Sheet does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Dampney Company, Inc.

**END OF DOCUMENT**