



Endcor 8898-0402
SDS Preparation Date (mm/dd/yyyy): 03/20/2023

Page 1 of 9

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label: Endcor Stainless Steel
Product Code(s): 8898-0402
Recommended use of the chemical and restrictions on use: self priming coating
Use pattern: Professional use only.
Recommended restrictions: None known.
Chemical family : Mixture

Name, address, and telephone number of the manufacturer:
Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A. 02149

Email: sales@dampney.com
Supplier's Telephone #: (617) 389-2805
24 Hr. Emergency Tel #: Chemtrec 1-800-424-9300 (Within Continental U.S.)

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical
Metallic Gray liquid. Solvent odor.

Most important hazards: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification:

Flammable Liquid – Category 2
Serious Eye Damage/eye irritation – Category 2A
Specific Target Organ Toxicity – Single Exposure – Category 3 (central nervous system)
Specific Target Organ Toxicity - Single Exposure – Category 3 (Narcotic effects)
Specific Target Organ Toxicity - Single Exposure – Category 3 (Respiratory system)
Aspiration Hazard – Category 1
Hazardous to the aquatic environment – long term hazard – Category 3
Carcinogen – Category 2
Label elements

Hazard pictogram(s)



Signal Word

DANGER!

Hazard statement(s)

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

Precautionary statement(s)

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical, ventilating, lighting, mixing, application equipment.



SAFETY DATA SHEET

P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust, fume, gas, mist, vapours, or spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection, and face protection.
P281 Use personal protective gloves, protective clothing, eye protection, and face protection.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or hospital emergency room.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER, doctor, or hospital emergency room if you feel unwell.
P331 Do NOT induce vomiting.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P370 + P378 In case of fire: Use dry chemical, CO₂, water spray (fog) or foam to extinguish.

Storage

P403 + P233 + P235 (S) Store in a cool, well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal

P501 Dispose of contents and empty container in accordance with local, state and federal regulations.

Other hazards

No OSHA defined hazard classes.
Other hazards which do not result in classification:
Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS #	Concentration
Tert-Butyl Acetate	540-88-5	11.84
Mineral Spirits	64742-47-8	9.64
Solvent Naphtha	64742-95-6	7.26
Chromium	7440-47-3	1.18
Nickel Compounds	N/A	0.83
Ethyl Benzene	100-41-4	0.11

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact: Immediately flush with plenty of water, while removing contaminated clothing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Eye contact: For eye contact, flush with running water for at least 15 minutes. If eye irritation persists: get medical advice/attention.

Most important symptoms and effects, both acute and delayed

: Causes skin irritation. Redness, swelling, itching and dryness. May cause respiratory irritation. May cause coughing and breathing difficulties. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause headache,



SAFETY DATA SHEET

nausea, dizziness and other symptoms of central nervous system depression. Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis. May cause damage to the central nervous system through prolonged or repeated exposure if inhaled. Suspected of causing cancer.

Indication of any immediate medical attention and special treatment needed
 : Treat symptomatically. This product is a CNS depressant.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Carbon dioxide (CO2); Dry chemical; Alcohol resistant foam; Water fog. .

Unsuitable extinguishing media: Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability: Highly flammable liquid and vapour. Vapours may ignite explosively. Vapours are heavier than air and may spread along floors. Static discharge, impact, friction, and heat may ignite exposed chemical material.

Flammability classification (OSHA 29 CFR 1910.106): Flammable Liquids - Category 2

Hazardous combustion products:

Carbon dioxide, carbon monoxide and other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures: Do not breathe fumes or vapours. Move containers from fire area if safe to do so. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions :Do not allow material to contaminate ground water system. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

Methods and material for containment and cleaning up: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools and equipment in the clean-up process. Avoid breathing mist or vapours. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contact the proper local authorities. Refer to Section 13 for disposal of contaminated material.

Special spill response procedures: In case of a transportation accident, contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. EPA/CERCLA

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/clothing and eye/face protection. Use only in well-ventilated areas. Do not breathe the mist or vapor. Avoid contact with skin, eyes and clothing. Keep container tightly closed. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Keep away from flames and hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharges. Ground all equipment during handling.

Conditions for safe storage: Keep container tightly closed. Store in cool/well-ventilated place. Store locked up. Keep cool. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Empty containers may contain hazardous residues.

Incompatible materials: Strong oxidizers, acids and bases.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

Chemical Name	ACGIH TLV		OSHA PEL	
	TWA	STEL	PEL	STEL
Tert-Butyl Acetate	200 ppm	N/Av	200 ppm (950 mg/m ³)	N/Av
Mineral Spirits	100 ppm	N/Av	100 ppm (400 mg/m ³)	N/Av
Solvent Naphtha	N/Av	N/Av	N/Av	N/Av
Chromium	0.5 mg/m ³	N/Av	1 mg/m ³	N/Av



SAFETY DATA SHEET

Nickel Compounds	1.5 mg/m ³	N/Av	N/Av	N/Av
Ethyl Benzene	20 ppm	N/Av	100 ppm (435 mg/m3)	N/Av

Exposure controls

Ventilation and engineering measures: Use only in well-ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection: If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection specialists.

Skin protection: Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. Advice should be sought from glove suppliers.

Eye / face protection: Wear chemical goggles.

Other protective equipment: Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations: Do not breathe the mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Metallic Gray liquid.
Odour:	Solvent odor.
Odour threshold:	Not available.
pH:	No information available.
Melting/Freezing point:	Not available.
Initial boiling point and boiling range:	208.4°F – 388.0°F
Flash point:	39.2°F
Flashpoint (Method):	Closed cup
Evaporation rate (BuAe = 1):	0.294 times faster than n-Butyl Acetate
Flammability (solid, gas):	Not applicable.
Lower flammable limit (% by vol.) :	1.0%
Upper flammable limit (% by vol.) :	12.8%
Oxidizing properties:	None known.
Explosive properties	Not explosive
Vapour pressure:	Not available
Vapour density:	Heavier than air
Relative density / Specific gravity:	1.29519
Weight per gallon:	10.8 lbs
Auto-ignition temperature:	Not available.
Decomposition temperature:	No information available.
Volatiles (% by weight):	31.0
Volatiles (% by volume):	50.0%
Volatile organic Compounds (VOC's):	2.49 lbs/gal
Other physical/chemical comments:	None known or reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity:	Not normally reactive.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	Hazardous polymerization does not occur.
Conditions to avoid:	Open flames, sparks, high heat, direct sunlight, and close proximity to incompatible substances. Do not use in areas without adequate ventilation.
Incompatible materials:	Strong oxidizers, acids and bases.
Hazardous decomposition products:	See Section 5 (Fire Fighting Measures).

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation:	YES
Routes of entry skin & eye:	YES



Endcor 8898-0402
 SDS Preparation Date (mm/dd/yyyy): 03/20/2023

SAFETY DATA SHEET

Routes of entry Ingestion: YES
Routes of exposure skin absorption: YES
Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation: May cause respiratory tract irritation. Symptoms may include sore throat, running nose and shortness of breath. May cause headache, nausea, dizziness and other symptoms of central nervous system depression.

Sign and symptoms ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin: Causes skin irritation.

Sign and symptoms eyes: Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

Potential Chronic Health Effects:

Prolonged exposure can cause central nervous system effects.

Mutagenicity: Not expected to be mutagenic in humans.

Carcinogenicity: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Carcinogenicity- Category 2 Suspected of causing cancer.

Reproductive effects & Teratogenicity: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: None.

Sensitization to material: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects: This material is classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012). Classification: Specific target organ toxicity, single exposure - Category 3. May cause drowsiness or dizziness. May cause respiratory irritation.

Specific target organ toxicity (STOT), repeated exposure - Category 2 May cause damage to the central nervous system through prolonged or repeated exposure if inhaled.

Medical conditions aggravated by overexposure: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials: No information available.

Toxicological data: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data. See below for toxicological data on the substance.

Chemical name	LC50 inhalation rat	LD50	
		(Oral, rat)	(Rabbit, dermal)
Tert-Butyl Acetate	>2,230 mg/m3 (4 hours)	4,100 mg/kg	>2,000 mg/kg
Mineral Spirits	5,000 mg/m3 (8 hours)	>5,000 mg/kg	>5,000 mg/kg
Solvent Naphtha	6,193 mg/m3 (4 hours)	492 mg/kg	> 3,160 mg/kg
Chromium	5.41 mg/l (4 hours)	>3,400 mg/kg	N/Av
Nickel Compounds	N/Av	N/Av	N/Av
Ethyl Benzene	17.4 mg/l (4 hours)	3,500 mg/kg	15,380 mg/kg

Other important toxicological hazards: None reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: Contains material that may be harmful in the environment. Do not allow material to contaminate ground water system. See data for individual ingredient ecotoxicity data.

Ecotoxicity data:

Ingredients	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Tert-Butyl Acetate	540-88-5	240 mg/L (Rainbow trout)	N/Av	None.
Mineral Spirits	64742-47-8	N/Av	N/Av	None.
Solvent Naphtha	64742-95-6	9.22 mg/L (mykiss)	N/Av	None.



SAFETY DATA SHEET

Chromium	7440-47-3	33 – 71.9 mg/l (Guppy)	N/Av	None.
Nickel Compound	N/A	N/Av	N/Av	None.
Ethyl Benzene	100-41-4	4.2 mg/l (Rainbow trout)	1.13 mg/L 30 days	None.

Ingredients	CAS No	Toxicity to Daphnia		
		EL50 / 48h	NOEC / 21 day	M Factor
Tert-Butyl Acetate	540-88-5	340 mg/L (Daphnia magna)	N/Av	None.
Mineral Spirits	64742-47-8	N/Av	N/Av	None.
Solvent Naphtha	64742-95-6	3.2 mg/L (Daphnia magna)	N/Av	None.
Chromium	7440-47-3	N/Av	N/Av	None.
Nickel Compound	N/A	N/Av	N/Av	None.
Ethyl Benzene	100-41-4	1.81 mg/l (Daphnia magna)	N/Av	None.

Ingredients	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
tert-Butyl Acetate	540-55-5	16.0 mg/L (Green Algae)	2.3 mg/L (Green Algae)	None.
Mineral Spirits	64742-47-8	N/Av	N/Av	None.
Solvent Naphtha	64742-95-6	N/Av	N/Av	N/Av
Chromium	7440-47-3	N/Av	N/Av	None.
Nickel Compound	N/A	N/Av	N/Av	None.
Ethyl Benzene	100-41-4	3.6 mg/L/96hr (Green Algae)	3.4 mg/L/96hr	None.

Persistence and degradability: No data is available on the product itself.

Bioaccumulation potential: No data is available on the product itself.

Mobility in soil: No data is available on the product itself.

Other Adverse Environmental effects: None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

Methods of Disposal: Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Hazard class(es)	Packing Group	Label
49CFR/DOT Additional information	UN1263	Paint	3	II	
When transported as a limited quantity the maximum net capacity specified in 173.150(b)(2) of the subchapter 49CFR for inner packagings may be increased to 5L (1.3 gallons) 172.102(C)(1)(149) special provision 149.					



Dampney Company, Inc.
 85 Paris Street
 Everett, Massachusetts, U.S.A 02149
 Email: sales@dampney.com
 Telephone: (617) 389 2805

Endcor 8898-0402
 SDS Preparation Date (mm/dd/yyyy): 03/20/2023

Page 7 of 9

SAFETY DATA SHEET

TDG Additional information	UN1263	PAINT	3	II	
	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass.				
IMDG Additional information	UN1263	Paint	3	II	
	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass.				
ICAO/IATA Additional information	UN1263	Paint	3	II	
	Refer to the appropriate Packing Instruction, prior to shipping this material.				

Special precautions for user: Appropriate advice on safety must accompany the package.

Environmental hazards: See ECOLOGICAL INFORMATION, Section 12.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity (RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Tert-Butyl Acetate	540-88-5	Yes	5,000 lb final RQ (listed under Butyl Acetate) 2,270 kg final RQ (listed under Butyl Acetate)	None.	No	N/Ap
Mineral Spirits	64742-47-8	Yes	None	None.	No	N/Ap
Solvent Naphtha	64742-95-6	Yes	None.	None.	No	N/Ap
Chromium	7440-47-3	Yes	5,000 lb/2,270 kg	None.	Yes	0.1%
Nickel Compound	N/A	Yes	N/Ap	None.	Yes	0.3%
Ethyl Benzene	100-41-4	Yes	1,000 lb/454 kg	None.	Yes	0.1%

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Immediate (Acute) health hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Tert-Butyl Acetate	540-88-5	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Mineral Spirits	64742-47-8	No	N/Ap	No	No	No	No	No	No
Solvent Naphtha	64742-95-6	No	N/Ap	No	No	No	No	No	No



SAFETY DATA SHEET

Chromium	7440-47-3	Yes	Cancer; male; female; Developmental (applies only to hexavalent compounds)	Yes	Yes	Yes	Yes	Yes	Yes
Nickel Compound	N/A	Yes	Cancer	Yes	Yes	Yes	Yes	Yes	Yes
Ethyl Benzene	100-41-4	Yes	Cancer	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

Canadian Environmental Protection Act (CEPA): All ingredients are present on the DSL.

International Information:

Components listed below are present on the following International Inventory list:

Ingredients	CAS #	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
tert-Butyl Acetate	540-88-5	208-760-7	Present	Present	(2)-735; (2)-731	KE-04180	Present	HSR001094
Mineral Spirits	64742-47-8	265-149-8	Present	Present	C00-781-75A	KE-12550	Present	Approved
Solvent Naphtha	64742-95-6	265-199-0	Present	Present	C005-106-94A	KE-31662	Present	HSR001503
Chromium	7440-47-3	231-157-5	Present	Present	C004-661-97A	KE-05970	Present	N/Av
Nickel Compounds	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Ethyl Benzene	100-41-4	202-849-4	Present	Present	(3)-60; (3)-28	KE-13532	Present	HSR001151

SECTION 16. OTHER INFORMATION

Legend:

- ACGIH: American Conference of Governmental Industrial Hygienists
- AICS: Australian Inventory of Chemical Substances
- ATE: Acute Toxicity Estimate
- CA: California
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- CSA: Canadian Standards Association
- DOT: Department of Transportation
- ECHA: European Chemicals Agency
- ECOTOX: U.S. EPA Ecotoxicology Database
- EINECS: European Inventory of Existing Commercial chemical Substances
- ENCS: Existing and New Chemical Substances
- EPA: Environmental Protection Agency
- HSDB: Hazardous Substances Data Bank
- IARC: International Agency for Research on Cancer
- IBC: Intermediate Bulk Container
- IECSC: Inventory of Existing Chemical Substances
- IMDG: International Maritime Dangerous Goods
- IOC: Inventory of Chemicals
- IUCLID: International Uniform Chemical Information Database
- KECI: Korean Existing Chemicals Inventory
- KECL: Korean Existing Chemicals List
- LC: Lethal Concentration
- LD: Lethal Dose
- MA: Massachusetts
- MN: Minnesota
- N/Av: Not Applicable
- N/A: Not Available
- NIOSH: National Institute of Occupational Safety and Health
- NJ: New Jersey



SAFETY DATA SHEET


NOEC: No observable effect concentration
NTP: National Toxicology Program
OECD: Organization for Economic Co-operation and Development
OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
PICCS: Philippine Inventory of Chemicals and Chemical Substances
RCRA: Resource Conservation and Recovery Act
RI: Rhode Island
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
SDS: Safety Data Sheet / Material Safety Data Sheet
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References:

1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2015.
2. International Agency for Research on Cancer Monographs, searched 2015.
3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2015 (Chempendium, HSDB and RTECs).
4. Material Safety Data Sheets from manufacturer.
5. US EPA Title III List of Lists - 2015 version.
6. California Proposition 65 List -2015 version

Preparation Date (mm/dd/yyyy): 03/20/2023

Other special considerations for handling: Provide adequate information, instruction and training for operators.

<p>Prepared by: Dampney Company, Inc. 85 Paris Street Everett MA 02149 U.S.A Telephone: (617) 389-2805 Please direct all inquiries to Dampney Company.</p>	
---	--

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Dampney Company, Inc. and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Dampney Company, Inc. expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this Safety Data Sheet does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Dampney Company, Inc.

END OF DOCUMENT