



Dampney Company, Inc.  
85 Paris Street  
Everett, Massachusetts, U.S.A. 02149  
Email: sales@dampney.com  
Telephone: (617) 389 2805

Thurmalox 245A VOC  
SDS Preparation Date (mm/dd/yyyy): 10/16/2024

## SAFETY DATA SHEET

Page 1 of 9

### SECTION 1. IDENTIFICATION

Product identifier used on the label: Thurmalox 245 (A)C  
Product Code(s): 245(A)C  
Recommended use of the chemical and restrictions on use: High Temperature Primer, VOC Compliant  
Use pattern: Professional Use Only  
Recommended restrictions: None Known.  
Chemical family: Mixture.

Name, address, and telephone number of the manufacturer:  
Dampney Company, Inc.  
85 Paris Street  
Everett, Massachusetts, U.S.A. 02149

Email: sales@dampney.com

Supplier's Telephone: (617) 389-2805  
24 Hr. Emergency Tel: Chemtrec 1-800-424-9300 (Within Continental U.S.)

### SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical  
Dark Gray Liquid. Solvent odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Hazard classification:

Flammable Liquids - Category 3  
Skin Irritation - Category 2  
Eye Damage/Irritation - Category 2B  
Carcinogenicity- Category 2  
Reproductive Toxicity - Category 2  
Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory)  
Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects

Label elements

Hazard pictogram(s)



Signal Word  
Warning.

Hazard statement(s)  
H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H320 Causes eye irritation.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging the unborn child.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness and dizziness.

Precautionary statement(s)  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.



Thurmalox 245A VOC  
SDS Preparation Date (mm/dd/yyyy): 10/16/2024

Page 2 of 9

## SAFETY DATA SHEET

P261 Avoid breathing vapors or mists.  
P271 Use only outdoors or in a well-ventilated area.  
P264 Wash thoroughly after handling.  
P280 Wear protective gloves/clothing and eye/face protection.  
P308 + P311 If exposed or concerned: Get medical advice/attention.

### Response:

P303 + P361 + P331 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P361 Take off contaminated clothing and wash it before reuse.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: get medical advice/attention.  
P304 + P340 + P312 IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.  
P370 + P378 In case of fire: Use water fog, dry chemical, CO2 or 'alcohol' foam for extinction.

### Storage:

P403 + P233 + P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
Store locked up.

### Disposal:

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Other hazards

No OSHA defined hazard classes.

### Other hazards which do not result in classification:

May be sensitive to static discharge. Burning produces obnoxious and toxic fumes.  
Ingestion can cause gastrointestinal irritation, nausea, and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

| Chemical name          | Common name and synonyms                         | CAS #     | Concentration (% by weight) |
|------------------------|--------------------------------------------------|-----------|-----------------------------|
| Methyl isobutyl ketone | 4-methylpentan-2-one Isobutyl methyl ketone MIBK | 108-10-1  | 13.82                       |
| Xylene                 | Dimethylbenzene Methyltoluene Xylol              | 1330-20-7 | 12.24                       |
| Methyl n-amyl ketone   | 2-heptanone                                      | 110-43-0  | 7.62                        |
| Ethylbenzene           | Ethylbenzol Phenylethane                         | 100-41-4  | 3.10                        |

## SECTION 4. FIRST-AID MEASURES

### Description of first aid measures

**Ingestion:** IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

**Inhalation:** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

**Skin contact:** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

**Eye contact:** In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.

Most important symptoms and effects, both acute and delayed: May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. May cause drowsiness and dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness, and other central nervous system effects. Causes skin irritation. Symptoms may include redness, itching and swelling. Causes eye irritation. Symptoms may include tearing, redness, and discomfort. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Suspected of damaging the unborn child. Suspected of causing cancer.

Indication of any immediate medical attention and special treatment needed: Treat symptomatically. This product is a CNS depressant.



Dampney Company, Inc.  
85 Paris Street  
Everett, Massachusetts, U.S.A. 02149  
Email: sales@dampney.com  
Telephone: (617) 389 2805

Thurmalox 245A VOC  
SDS Preparation Date (mm/dd/yyyy): 10/16/2024

Page 3 of 9

## SAFETY DATA SHEET

### SECTION 5. FIRE-FIGHTING MEASURES

#### Extinguishing media

*Suitable extinguishing media:* Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

*Unsuitable extinguishing media:* Do not use water jet, as this may spread burning material.

Special hazards arising from the substance or mixture / Conditions of flammability: Flammable liquid and vapour. Keep away from heat and flame. This product will accumulate static charge by flow, splashing or agitation. Vapors may travel considerable distance to a source of ignition and flash back. Vapours are heavier than air and collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106): Flammable Liquids - Category 3

Hazardous combustion products: Carbon oxides; Other unidentified organic compounds.

#### Special protective equipment and precautions for firefighters

*Protective equipment for fire-fighters:* Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

*Special fire-fighting procedures:* Move containers from fire area if safe to do so. Use water spray to cool unopened containers. Avoid spreading burning liquid with water spray used for cooling purposes. Do not allow run-off from fire fighting to enter drains or water courses. Prevent fire extinguishing water from contaminating surface water or the ground water system. Dike for water control.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapour or mist. Restrict access to area until completion of clean-up. Remove all sources of ignition. All persons dealing with the clean-up should wear the appropriate personal protective equipment. For personal protection see section 8.

Environmental precautions: Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Contaminated absorbent material may pose the same hazards as the spilled product. Pick up and transfer to properly labeled containers. Contact the proper local authorities.

Special spill response procedures: In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300.

#### EPA/CERCLA Reportable quantity (RQ):

Xylene (100 lbs / 45.4 kg)

Ethylbenzene (1000 lbs / 454 kg)

Methyl isobutyl ketone (5000 lbs / 2270 kg)

### SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat and flame. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Bond and ground transfer containers and equipment. Use explosion-proof electrical and ventilating equipment. Use non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection. Avoid breathing vapour or mist. Do not ingest. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials.

Conditions for safe storage: Store in well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Store away from incompatibles and out of direct sunlight. Take measures to prevent the buildup of electrostatic charge. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials: Strong oxidizers, acids and bases.

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:



Dampney Company, Inc.  
85 Paris Street  
Everett, Massachusetts, U.S.A.02149  
Email: sales@dampney.com  
Telephone: (617) 389 2805

Thurmalox 245A VOC  
SDS Preparation Date (mm/dd/yyyy): 10/16/2024

Page 4 of 9

#### SAFETY DATA SHEET

| Chemical Name          | ACGIH TLV |         | OSHA PEL                         | PEL STEL |
|------------------------|-----------|---------|----------------------------------|----------|
|                        | TWA       | STEL    |                                  |          |
| Methyl isobutyl ketone | 20 ppm    | 75 ppm  | 100 ppm (410 mg/m <sup>3</sup> ) | N/Av     |
| Xylene                 | 100 ppm   | 150 ppm | 100 ppm (435 mg/m <sup>3</sup> ) | N/Av     |
| Methyl n-amyl ketone   | 50 ppm    | N/Av    | 100 ppm (465 mg/m <sup>3</sup> ) | N/Av     |
| Ethylbenzene           | 20 ppm    | N/Av    | 100 ppm (435 mg/m <sup>3</sup> ) | N/Av     |

#### Exposure controls

Ventilation and engineering measures: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection: If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection: Wear protective gloves. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection: Chemical splash goggles are recommended.

Other protective equipment: Ensure that eyewash stations and safety showers are close to the workstation location.

Other equipment may be required depending on workplace standards.

General hygiene considerations: Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                         |                                           |
|-----------------------------------------|-------------------------------------------|
| Appearance                              | : Dark gray liquid                        |
| Odour                                   | : Solvent odor.                           |
| Odour threshold                         | : N/Av                                    |
| Ph                                      | : N/Av                                    |
| Melting/Freezing point                  | : N/Av                                    |
| Initial boiling point and boiling range | : 243.2-305.6°C (469.76 - 582.08°F)       |
| Flash point                             | : 57-125°F (13.8-51.6°C)                  |
| Flashpoint (Method)                     | : Closed cup                              |
| Evaporation rate (BuAe = 1)             | : 0.065 times slower than n-Butyl acetate |
| Flammability (solid, gas)               | : N/Av                                    |
| Lower flammable limit (% by vol.)       | : 1.0%                                    |
| Upper flammable limit (% by vol.)       | : 7.9%                                    |
| Explosive properties                    | : Not explosive                           |
| Vapour pressure Vapour density          | : >1                                      |
| Relative density / Specific gravity     | : 1.165                                   |
| Weight per gallon                       | : 9.32 lbs                                |
| Auto-ignition temperature               | : N/Av                                    |
| Viscosity                               | : 300 cSt at 40°C 37.51%                  |
| Volatiles (% by weight)                 | : 37.51                                   |
| Volatiles (% by volume)                 | : 52.5                                    |
| Volatile organic Compounds (VOC's)      | : 3.49lbs/gal                             |

Other physical/chemical comments : None reported by the manufacturer.

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not normally reactive.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Hazardous polymerization does not occur. May be sensitive to static discharge.

Conditions to avoid: Keep away from heat, sparks and flame. Take precautionary measures against static discharge. Keep away from direct



Thurmalox 245A VOC  
SDS Preparation Date (mm/dd/yyyy): 10/16/2024

Page 5 of 9

## SAFETY DATA SHEET

sunlight. Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials.  
Incompatible materials: Strong oxidizers, acids and bases.  
Hazardous decomposition products: None reported by the manufacturer. In the event of fire the following can be released: Carbon oxides;  
Other unidentified organic compounds.

### SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES  
Routes of entry skin & eye : YES  
Routes of entry Ingestion : YES  
Routes of exposure skin absorption : NO

Potential Health Effects: **Signs and symptoms of short-term (acute) exposure**

*Sign and symptoms Inhalation:* May cause respiratory irritation. Symptoms may include sore throat, running nose and shortness of breath. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness.

*Sign and symptoms ingestion:* Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Causes symptoms similar to those listed for inhalation.

*Sign and symptoms skin:* This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Skin Irritation - Category 2 Causes skin irritation. Symptoms may include mild redness and swelling.

*Sign and symptoms eyes:* This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Eye Damage/Irritation - Category 2B Causes eye irritation. Symptoms may include tearing, redness and discomfort.

Potential Chronic Health Effects: Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Mutagenicity: Not expected to be mutagenic in humans.

Carcinogenicity: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Carcinogenicity- Category 2 Suspected of causing cancer.

Reproductive effects & Teratogenicity: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Reproductive Toxicity - Category 2 Suspected of damaging the unborn child.

Sensitization to material: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects: Eyes, skin, respiratory system, digestive system, central nervous system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification:

Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory) May cause respiratory irritation.

Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects May cause drowsiness and dizziness.

Not classified as a specific target organ toxicity - repeated exposure. Not classified as a specific target organ toxicity - repeated exposure.

Medical conditions aggravated by overexposure: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials: None reported by the manufacturer.

Toxicological data: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data. The calculated ATE values for this mixture are: ATE oral = 4798.17 mg/kg  
ATE dermal =16714.90 mg/kg  
ATE inhalation (vapours) = 34.42 mg/L

| Chemical name          | LC50(4hr)<br>inh, rat          | LD50        |                  |
|------------------------|--------------------------------|-------------|------------------|
|                        |                                | (Oral, rat) | (Rabbit, dermal) |
| Methyl isobutyl ketone | 3000 ppm (12.29 mg/L) (vapour) | 2080 mg/kg  | > 3000 mg/kg     |
| Xylene                 | 6350 ppm (27.6 mg/L) (vapours) | 3253 mg/kg  | 12 180 mg/kg     |
| Methyl n-amyl ketone   | >16 mg/L                       | 1670 mg/kg  | 10,300 mg/kg     |
| Ethylbenzene           | 4000 ppm (17.4 mg/L) (vapour)  | 3500 mg/kg  | 15 380 mg/kg     |

Other important toxicological hazards: None known or reported by the manufacturer.



Thurmalox 245A VOC  
SDS Preparation Date (mm/dd/yyyy): 10/16/2024

SAFETY DATA SHEET

Page 6 of 9

**SECTION 12. ECOLOGICAL INFORMATION**

Ecotoxicity: Should not be released into the environment.

See the following tables for the substance's ecotoxicity data.

*Ecotoxicity data:*

| Ingredients            | CAS No    | Toxicity to Fish          |                   |          |
|------------------------|-----------|---------------------------|-------------------|----------|
|                        |           | LC50 / 96h                | NOEC / 21 day     | M Factor |
| Methyl isobutyl ketone | 108-10-1  | 780 mg/L (Fathead minnow) | N/Av              | None.    |
| Xylene                 | 1330-20-7 | 8.2 mg/L (Rainbow trout)  | N/Av              | None.    |
| Methyl n-amyl ketone   | 110-43-0  | 131 mg/L (Fathead minnow) | n/av              | none     |
| Ethylbenzene           | 100-41-4  | 4.2 mg/L (Rainbow trout)  | 1.13 mg/L/30 days | None.    |

| Ingredients            | CAS No    | Toxicity to Daphnia             |               |          |
|------------------------|-----------|---------------------------------|---------------|----------|
|                        |           | EC50 / 48h                      | NOEC / 21 day | M Factor |
| Methyl isobutyl ketone | 108-10-1  | > 200 mg/L (Daphnia magna)      | 30 mg/L       | None.    |
| Xylene                 | 1330-20-7 | 3.2 - 9.56 mg/L (Daphnia magna) | N/Av          | None.    |
| Methyl n-amyl ketone   | 110-43-0  | n/av                            | n/av          | none     |
| Ethylbenzene           | 100-41-4  | 1.81 mg/L (Daphnia magna)       | N/Av          | None.    |

| Ingredients            | CAS No    | Toxicity to Algae                 |                   |          |
|------------------------|-----------|-----------------------------------|-------------------|----------|
|                        |           | EC50 / 96h or 72h                 | NOEC / 96h or 72h | M Factor |
| Methyl isobutyl ketone | 108-10-1  | 400 mg/L/96hr (Green algae)       | N/Av              | None.    |
| Xylene                 | 1330-20-7 | 3.2 - 4.9 mg/L/72hr (Green algae) | N/Av              | None.    |
| Methyl n-amyl ketone   | 110-43-0  | 75.5 mg/L (Green algae)           | n/av              | none     |
| Ethylbenzene           | 100-41-4  | 3.6 mg/L/96hr (Green algae)       | 3.4 mg/L/96hr     | None.    |

Persistence and degradability: No data is available on the product itself.

Bioaccumulation potential: No data is available on the product itself.

| Components             | Partition coefficient n-octanol/water (log Kow) | Bioconcentration factor (BCF) |
|------------------------|-------------------------------------------------|-------------------------------|
| Methyl isobutyl ketone | 1.31                                            | 3.98                          |
| Xylene                 | 3.12 - 3.2                                      | 0.6 - 15                      |
| Methyl n-amyl ketone   | 1.98                                            |                               |
| Ethylbenzene           | 3.15                                            | 15 species: fish              |

Mobility in soil: No data is available on the product itself.

Other Adverse Environmental effects: None known or reported by the manufacturer.

**SECTION 13. DISPOSAL CONSIDERATIONS**

Handling for Disposal: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

Methods of Disposal: Dispose in accordance with all applicable regulations.

RCRA: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

**SECTION 14. TRANSPORTATION INFORMATION**



Dampney Company, Inc.  
85 Paris Street  
Everett, Massachusetts, U.S.A.02149  
Email: sales@dampney.com  
Telephone: (617) 389 2805

Thurmalox 245A VOC  
SDS Preparation Date (mm/dd/yyyy): 10/16/2024

Page 7 of 9

# SAFETY DATA SHEET

| Regulatory Information           | UN Number                                                                                                                                                                                                                                                                                                            | UN proper shipping name                                                                                          | Transport hazard class(es) | Packing Group | Label                                                                                 |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|----------------------------|---------------|---------------------------------------------------------------------------------------|
| 49CFR/DOT                        | UN1263                                                                                                                                                                                                                                                                                                               | PAINT                                                                                                            | 3                          | II            |    |
| Additional information           | When transported as a limited quantity the maximum net capacity specified in 173.150(b)(2) of the subchapter 49CFR for inner packagings may be increased to 5L (1.3 gallons) 172.102(C)(1)(149) special provision 149.                                                                                               |                                                                                                                  |                            |               |                                                                                       |
| TDG                              | UN1263                                                                                                                                                                                                                                                                                                               | PAINT                                                                                                            | 3                          | II            |    |
| Additional information           | May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass. ERG #128                                                                                                                                                                    |                                                                                                                  |                            |               |                                                                                       |
| IMDG                             | UN1263                                                                                                                                                                                                                                                                                                               | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) | 3                          | II            |    |
| Additional information           | May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass. May be shipped as Limited Quantity when transported in containers no larger than 5.0 kg (11 lbs); in packages not exceeding 30 kg (66 lbs) gross mass. |                                                                                                                  |                            |               |                                                                                       |
| ICAO/IATA                        | UN1263                                                                                                                                                                                                                                                                                                               | Paint                                                                                                            | 3                          | II            |  |
| ICAO/IATA Additional information | Refer to the ICAO/IATA Packing Instruction                                                                                                                                                                                                                                                                           |                                                                                                                  |                            |               |                                                                                       |

Special precautions for user: Keep away from heat, sparks and open flame. - No smoking.  
Environmental hazards: See ECOLOGICAL INFORMATION, Section 12.  
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not available.

## SECTION 15 - REGULATORY INFORMATION

US Federal Information: Components listed below are present on the following U.S. Federal chemical lists:

| Ingredients            | CAS #     | TSCA Inventory | CERCLA Reportable Quantity (RQ) (40 CFR 117.302): | SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355: | SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical de minimus Concentration |      |
|------------------------|-----------|----------------|---------------------------------------------------|----------------------------------------------------------------------|----------------------------------------------------------------------------------------|------|
| Methyl isobutyl ketone | 108-10-1  | Yes            | 5000 lb/ 2270 kg                                  | None.                                                                | Yes                                                                                    | 1%   |
| Xylene                 | 1330-20-7 | Yes            | 100 lb/ 45.4 kg                                   | None.                                                                | Yes                                                                                    | 1%   |
| Methyl n-amyl ketone   | 110-43-0  | Yes            | N/Ap                                              | N/Av                                                                 | No                                                                                     | N/Ap |
| Ethylbenzene           | 100-41-4  | Yes            | 1000 lb/ 454 kg                                   | None.                                                                | Yes                                                                                    | 0.1% |

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws: The following chemicals are specifically listed by individual States:

| Ingredients            | CAS #    | California Proposition 65 |                       | State "Right to Know" Lists |     |     |     |     |     |
|------------------------|----------|---------------------------|-----------------------|-----------------------------|-----|-----|-----|-----|-----|
|                        |          | Listed                    | Type of Toxicity      | CA                          | MA  | MN  | NJ  | PA  | RI  |
| Methyl isobutyl ketone | 108-10-1 | Yes                       | Cancer; Developmental | Yes                         | Yes | Yes | Yes | Yes | Yes |



Dampney Company, Inc.  
85 Paris Street  
Everett, Massachusetts, U.S.A.02149  
Email: sales@dampney.com  
Telephone: (617) 389 2805

Thurmalox 245A VOC  
SDS Preparation Date (mm/dd/yyyy): 10/16/2024

Page 8 of 9

#### SAFETY DATA SHEET

|                      |           |     |        |     |     |     |     |     |     |
|----------------------|-----------|-----|--------|-----|-----|-----|-----|-----|-----|
| Xylene               | 1330-20-7 | No  | N/Ap   | Yes | Yes | Yes | Yes | Yes | Yes |
| Methyl n-amyl ketone | 110-43-0  | No  | N/Ap   | Yes | Yes | Yes | Yes | Yes | Yes |
| Ethylbenzene         | 100-41-4  | Yes | Cancer | Yes | Yes | Yes | Yes | Yes | Yes |

Canadian Information: Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS Classification: See Section 2.

International Information: Components listed below are present on the following International Inventory list:

| Ingredients            | CAS #     | European EINECS | Australia AICS | Philippines PICCS | Japan ENCS     | Korea KECI/KECL | China IECSC | New Zealand IOC |
|------------------------|-----------|-----------------|----------------|-------------------|----------------|-----------------|-------------|-----------------|
| Methyl isobutyl ketone | 108-10-1  | 203-550-1       | Present        | Present           | (2)-542        | KE-24725        | Present     | HSR001194       |
| Xylene                 | 1330-20-7 | 215-535-7       | Present        | Present           | (3)-60; (3)-3  | KE-35427        | Present     | HSR000983       |
| Methyl n-amyl ketone   | 110-43-0  | 203-767-1       | Present        | Present           | Not listed     | Not listed      | Present     | Not listed      |
| Ethylbenzene           | 100-41-4  | 202-849-4       | Present        | Present           | (3)-60; (3)-28 | KE-13532        | Present     | HSR001151       |

#### SECTION 16. OTHER INFORMATION

##### Legend:

ACGIH: American Conference of Governmental Industrial Hygienists  
AICS: Australian Inventory of Chemical Substances  
CA: California  
CAS: Chemical Abstract Services  
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980  
CFR: Code of Federal Regulations  
CSA: Canadian Standards Association  
DOT: Department of Transportation  
EC50: Effective Concentration 50%.  
EINECS: European Inventory of Existing Commercial chemical Substances  
ENCS: Existing and New Chemical Substances  
EPA: Environmental Protection Agency  
HMIS: Hazardous Materials Identification System  
HSDB: Hazardous Substances Data Bank  
IARC: International Agency for Research on Cancer  
IECSC: Inventory of Existing Chemical Substances  
IMDG: International Maritime Dangerous Goods  
Inh: Inhalation  
KECI: Korean Existing Chemicals Inventory  
KECL: Korean Existing Chemicals List  
LC: Lethal Concentration  
LD: Lethal Dose  
N/Ap: Not Applicable  
N/Av: Not Available  
NFPA: National Fire Protection Association  
NJ: New Jersey  
NIOSH: National Institute of Occupational Safety and Health  
NOEC: No observable effect concentration  
NTP: National Toxicology Program  
OECD: Organization for Economic Co-operation and Development  
OSHA: Occupational Safety and Health Administration  
PA: Pennsylvania  
PEL: Permissible exposure limit  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
RCRA: Resource Conservation and Recovery Act  
RTECS: Registry of Toxic Effects of Chemical Substances  
SARA: Superfund Amendments and Reauthorization Act  
STEL: Short Term Exposure Limit  
TDG: Canadian Transportation of Dangerous Goods Act & Regulations  
TLV: Threshold Limit Values  
TPQ: Threshold Planning Quantity  
TSCA: Toxic Substance Control Act



Dampney Company, Inc.  
85 Paris Street  
Everett, Massachusetts, U.S.A. 02149  
Email: sales@dampney.com  
Telephone: (617) 389 2805

Thurmalox 245A VOC  
SDS Preparation Date (mm/dd/yyyy): 10/16/2024

Page 9 of 9

#### SAFETY DATA SHEET

TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Identification System

#### References:

Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2015 (Chempendium, RTECs, HSDB, INCHEM).  
OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015  
European Chemicals Agency, Classification Legislation, 2015 Material Safety Data Sheet from manufacturer.

Preparation Date (mm/dd/yyyy): 10/16/2024

Other special considerations for handling: Provide adequate information, instruction and training for operators.

Prepared by:  
Dampney Company, Inc.  
85 Paris Street  
Everett MA 02149 U.S.A  
Telephone: (617) 389-2805



#### DISCLAIMER

This Safety Data Sheet was prepared by Dampney Company, Inc. The information in the Safety Data Sheet is offered for consideration and guidance when exposed to this product. Dampney Company, Inc expressly disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Dampney Company, Inc.

END OF DOCUMENT