



Thurmalox 2804
SDS Preparation Date (mm/dd/yyyy): 03/25/2022

Page 1 of 6

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label: Thurmalox Waterborne Aluminum
Product Code(s): 2804

Recommended use of the chemical and restrictions on use

Use pattern : High temperature waterborne coating
: Professional Use Only
Recommended restrictions : None Known.

Chemical family : Mixture.

Name, address, and telephone number of the manufacturer:

Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A. 02149

Email: sales@dampney.com
Supplier's Telephone #: (617) 389-2805
24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.)

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical
Aluminum. Slight solvent odor.

Classification:
Skin irritation - Category 2
Eye irritation - Category 2A
Specific target organ toxicity – repeated exposure Category 2

Label elements

Hazard pictogram(s)



Signal Word

DANGER

Hazard statement(s)

H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H402 Harmful to aquatic life.

Prevention:

P233 Keep container tightly closed.
P260 Do not breathe dust, fume, gas, mist, vapours, or spray.
P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves, protective clothing, eye protection, and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.



Thurmalox 2804
SDS Preparation Date (mm/dd/yyyy): 03/25/2022

Page 2 of 6

SAFETY DATA SHEET

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER, doctor, or hospital emergency room.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment see first aid on this label.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry chemical, CO₂, water spray (fog) or foam to extinguish.

Storage:

P403 + P235 (S) Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents and empty container in accordance with local, state and federal regulations. Causes skin irritation

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical Name	CAS-No	Weight %*
1H-Imidazol-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-	95-38-5	1.98
Xylene	1330-20-7	1.71
Ethylbenzene	100-41-4	0.64

First aid measures for different exposure routes

SECTION 4. FIRST-AID MEASURES

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.
Eye contact Rinse thoroughly with plenty of water for at least 15 minutes. Consult a physician if irritation persists.
Skin contact Wash off immediately with soap and plenty of water. Get medical attention immediately if symptoms occur.
Inhalation Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion Most important symptoms/effects, acute and delayed. Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.
Suitable Extinguishing Media Alcohol resistant foam, Carbon dioxide (CO₂), Dry chemical. Cool containers / tanks with water spray.
Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

SECTION 5. FIRE-FIGHTING MEASURES

Specific hazards during firefighting Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products Oxides of carbon and various hydrocarbons.
Specific extinguishing methods Use a water spray to cool fully closed containers.
Protective Equipment and Precautions for Firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.
Personal precautions, protective equipment and emergency procedures

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions Eliminate all ignition sources. Maintain adequate ventilation to keep the exposure levels below the DELS.
Environmental precautions Report spills as required by local and federal regulations. Avoid contaminating ground and surface water
Methods for Containment Prevent further leakage or spillage if safe to do so. Dike spill area to contain liquid.
Methods for cleaning up Contain liquid and collect with a non-combustible material.

SECTION 7. HANDLING AND STORAGE



Thurmalox 2804
SDS Preparation Date (mm/dd/yyyy): 03/25/2022

Page 3 of 6

SAFETY DATA SHEET

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Avoid skin contact. Use with adequate ventilation. Keep away from heat, flames, and all other sources of ignition. Keep away from all sources of electricity such as electric motors and batteries.

Conditions for safe storage, including any incompatibilities Keep containers tightly closed in a cool, well-ventilated place.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters:

Chemical Name	ACGIH	OSHA	NIOSH
1H-Imidazol-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-	N/Av	N/Av	N/Av
Xylene	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m3	TWA: 100 ppm TWA: 435 mg/m3
Ethylbenzene	TWA: 20 ppm TWA: 87 mg/m3	TWA: 100 ppm TWA: 435 mg/m3	TWA: 100 ppm TWA: 435 mg/m3

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH: (National Institute for Occupational Safety and Health)

TWA: Time Weighted Average

Exposure controls

Engineering Measures Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aluminum Liquid
Odour	: Slight
pH	: 8.0
Melting/Freezing point	: N/Av
Boiling point	: 176.0°F (80.0°C)
Flash point	: N/Av
Evaporation rate (BuAe = 1)	: 0.02 times slower than n-Butyl Acetate
Lower flammable limit (% by vol.)	: 1.0
Upper flammable limit (% by vol.)	: 7.0
Volatile Weight	: 57.0%
Volatile Volume	: 69.0%
Vapour pressure Vapour density	: No information available
Specific gravity	: 1.18849
Weight per gallon	: 9.9 lbs
Solubility in water	: No information available
Auto-ignition temperature	: N/Av
VOC	: 0.71 lbs/gal

SECTION 10. STABILITY AND REACTIVITY

Reactivity Stable under recommended storage conditions

Chemical stability Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid Keep away from heat, flame and other potential ignition sources.



Thurmalox 2804
SDS Preparation Date (mm/dd/yyyy): 03/25/2022

Page 4 of 6

SAFETY DATA SHEET

Incompatible Materials Store away from strong acids or oxidizers.
Hazardous Decomposition Products
Carbon oxides. Fumes. Hydrocarbons.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Prolonged skin contact can cause redness and irritation. Severity depends on the amount and duration of exposure.
Vapors are irritating to eyes. Liquid contact will cause stinging and tearing.
Exposure to high vapour concentrations may cause nervous systems effects such as headache, nausea, and dizziness.
Aspiration into the lungs during swallowing may result in damage or death.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LD50 Inhalation
1H-Imidazol-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-	N/Av	N/Av	N/Av
Xylene 1330-20-7	= 4300 mg/kg (Rat)	= 1700 mg/kg (Rabbit)	= 5000 mg/m3 (Rat) 4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15433 mg/kg (Rabbit)	No data available

Aquatic Toxicity data: LC50 – Oncorhynchus mykiss (rainbow trout) – 7.63 mg/l – 96 hours

SECTION 12. ECOLOGICAL INFORMATION

NOEC – Pimephales promelas (fathead minnow) – 5.44 mg/l – 7 days
Persistence and degradability : Not available.
Bio-accumulative potential : This product is readily biodegradable.
Mobility : Accidental spillage may lead to penetration in the soil.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle in accordance with good industrial hygiene and safety practice.
Methods of Disposal : Dispose in accordance with all applicable regulations.

SECTION 14. TRANSPORTATION INFORMATION

Not regulated.

Special precautions for use: Protect from freezing.
U.S. Federal Regulations

SECTION 15 - REGULATORY INFORMATION

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 -Threshold Values %
Xylene	1330-20-7	1.71	1.0
Ethyl Benzene	100-41-4	0.64	0.1

SARA 311/312 Hazard Categories
Acute Health Hazard Yes



Thurmalox 2804
SDS Preparation Date (mm/dd/yyyy): 03/25/2022

Page 5 of 6

SAFETY DATA SHEET

Chronic Health Hazard Yes
Fire Hazard Yes

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA -Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb			X
Ethyl Benzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Xylene 1330-20-7	100lb		RQ 100 lb final RQ
Ethyl Benzene 100-41-4	1000lb		RQ 1000 lb final RQ

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Toluene -108-88-3	Developmental
Ethyl Benzene - 100-41-4	Carcinogen

US State Right to Know Laws:

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	X	X	X
Ethyl Benzene 100-41-4	X	X	X

SECTION 16. OTHER INFORMATION

NFPA

Health hazard 2
Flammability 0
Reactivity 0

Legend:

ACGIH: American Conference of Governmental Industrial Hygienists
AICS: Australian Inventory of Chemical Substances
CA: California
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
CSA: Canadian Standards Association
DOT: Department of Transportation
EC50: Effective Concentration 50%.
EINECS: European Inventory of Existing Commercial chemical Substances
ENCS: Existing and New Chemical Substances
EPA: Environmental Protection Agency
HMIS: Hazardous Materials Identification System
HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
IECSC: Inventory of Existing Chemical Substances
IMDG: International Maritime Dangerous Goods Inh: Inhalation
KECI: Korean Existing Chemicals Inventory
KECL: Korean Existing Chemicals List
LC: Lethal Concentration
LD: Lethal Dose



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A.02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 2804
SDS Preparation Date (mm/dd/yyyy): 03/25/2022

Page 6 of 6

SAFETY DATA SHEET

N/Ap: Not Applicable
N/Av: Not Available
NFPA: National Fire Protection Association
NJ: New Jersey
NIOSH: National Institute of Occupational Safety and Health
NOEC: No observable effect concentration
NTP: National Toxicology Program
OECD: Organisation for Economic Co-operation and Development
OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
PICCS: Philippine Inventory of Chemicals and Chemical Substances
RCRA: Resource Conservation and Recovery Act
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TPQ: Threshold Planning Quantity
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References:

Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2015 (Chempendium, RTECs, HSDB, INCHEM).
OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015
European Chemicals Agency, Classification Legislation, 2015 Material Safety Data Sheet from manufacturer.

Prepared by Dampney Company, Inc.
85 Paris Street
Everett, MA 02149

Tel. 617-389-2805
Fax. 617-389-0484
Email mail@dampney.com

Preparation Date (mm/dd/yyyy): 03/25/2022

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Dampney Company, Inc. 85 Paris Street Everett MA 02149 U.S.A Telephone: (617) 389-2805	
--	--

DISCLAIMER

The information and recommendations contained herein are based on data believed to be correct. However, Dampney makes no warranty expressed or implied regarding the accuracy of these data or results to be obtained from the use thereof. Dampney assumes no responsibility for personal injury or property damage caused by use of the material described herein. It is the responsibility of the purchaser or the user to ensure that this material is properly and safely used.

Last Page